

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

AUG 16 1992

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well  
☐ Oil Well ☐ Gas Well ☒ Other Injection Well

2. Name of Operator  
YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.  
105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
Unit L, 2455' FSL & 50' FWL, Sec. 7-T18S-R30E

5. Lease Designation and Serial No.  
LC-047269-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

West Loco Hills Unit

8. Well Name and No.  
Tract 1, Well #10

9. API Well No.  
30-015-27042

10. Field and Pool, or Exploratory Area  
Loco Hills-Q-G-SA

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Surface Casing  
5 1/2" Casing
- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☒ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded with Frank's rathole 3:30 PM 7-19-92. Resumed drilling 12-1/4" hole 12:15 PM 7-20-92. Ran 9 joints 8-5/8" 24# J-55 casing set 385'. Guide shoe set 385', insert float set 341'. Cemented w/300 sx "C" + 2% CaCl2 + 1/4# Celloseal (yield 1.32, wt 14.8). PD 7:15 PM 8-20-92. Bumped plug to 500 psi, float did not hold. Circulated 76 sacks to pit. WOC. Drilled out 1:15 PM 7-21-92. WOC 18 hrs. NU and tested to 1000 psi for 30 minutes. Reduced hole to 7-7/8" and resumed drilling. Notified BLM, no witnesses. TD 2900'. Reached TD 7-24-92. Ran 69 joints 5-1/2" 15.5# J-55 casing set 2900'. Guide shoe set 2900', float collar set 2857'. Cemented w/465 sx PSL "C" + 10# salt + 5# Gilsonite + 1/4#/sx Celloseal (yield 1.32, wt 14.6). PD 5:15 AM 7-25-92. Bumped plug to 1000 psi. Casing OK, float did not hold. Circulated 101 sacks cement. Marker #1 at 2577', #2 at 2139'. WOC 24 hrs.

ACCEPTED FOR RECORD

AS  
4 1992

CARLSBAD, NEW MEXIC

14. I hereby certify that the foregoing is true and correct

*[Signature]*

Title Production Supervisor

Date 7-27-92

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: