rm 3160-5 Jecember 1989)

2. Name of Operator

3. Address and Telephone No.

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. 7 ision 811 S. 1st Street

Artesia, NM 88210-2834

FORM APPROVED Russen No. 1004-0135

E	xpires:	Septe	mber	70.	1990
	Design			Senul	

LC-029420-13

E	xpires:	Septe	Tibe		
	Design			Senul	No.

Tribe Name

SUNDRY NO	OTICES A	ND REPORTS	ON WELLS	•	6. If Indian, Allottee or
					l .

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well XX Oil Well

	•
DECEIVE	8 Well Name and No.
	Dow "B" 33 Fed #1
,	9. API Well No.
NOV - 1 1996	30-015-27068
	10. Field and Pool, or Exploratory Area
an aam M	N/Wildcat Gravburg

4. Location of Weli (Footage, Sec., T., R., M., or Survey Description) H. County or Parish, State Unit Letter J 2180' FSL & 1980' FEL Sec 33 T-17-S R-31-E Eddy, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment Notice of Intent **New Construction** Recompletion Plugging Back Non-Routine Fracturing XX Subsequent Report Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*,

1) Load hole with mud

Spot 30 sx cement plug @ 5100'

Texaco Exploration and Production Company, Inc.

P. O. Box 3109, Midland, TX 79701 915-688-4816

Perforate 5½ casing @ 3885' Unable to pump into perforations at 1200psi Called BLM in Carlsbad, NM got approval by Joe Lara to spot cement plug across perforation & tag spot 25 sx cement plug @ 3937' W.O.C. Tag cement top @ 3777'

Perforate 5½ casing @ 1950' Squeeze W/65 sx W.O.C. Tag cement top @ 1830'

Perforate 5½ casing @ 703' Circulate cement to surface between 5-1/2 & 8-5/8 W/160 sx W.O.C. Tag cement top @ 564'

Spot 15 sx cement from 100' to surface Set PA marker 6)

Job Completed 10-09-96

Approved as to plugging of the well bown. Liability under bond is retained until surface restoration is completed,

Signod Mayney A Bassaco	Title <u>XI</u>	powieson	Date	10-9-96
(This space for Federal or State office used D. R. GLASS (ORIG. SGD.) DAVID R. GLASS	Title	PETROLEUM ENGINEER	Date	OCT 3 0 1996
Conditions of approval, if any:				

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction