

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-27091
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-7811
7. Lease Name or Unit Agreement Name Cedar Breaks "2" State
8. Well No. 1
9. Pool name or Wildcat Walters Lake (Bone Springs)
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3629' GL

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Mewbourne Oil Company
3. Address of Operator P.O. Box 5270 Hobbs, New Mexico 88241
4. Well Location Unit Letter G : 2130 Feet From The North Line and 1980 Feet From The East Line Section 2 Township 18S Range 30E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: Squeeze Existing Perforations <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Squeeze existing Bone Springs Perforations (6918'-7062') with  $\pm$  400 sacks Class "H" cement.
2. Drill out squeeze and test to 2000#.
3. Drill out float collar, shoe joint and guide shoe.
4. Shut well in and wait for rotary rig to deepen well.

RECEIVED

JUL 9 1993

C. L. D.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Erick W. Nelson TITLE Engineer DATE 07/09/93  
TYPE OR PRINT NAME Erick W. Nelson TELEPHONE NO. (505) 393-8905

(This space for State Use)

APPROVED BY ORIGINAL SIGNED BY MIKE WILLIAMS SUPERVISOR, DISTRICT II TITLE  DATE JUL 20 1993  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED BY

DATE