

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator SDX RESOURCES INC.		Lease ARTESIA METEX UT.		Well # 62	
Location of Well	Unit 1E	Section 30	Township 18	Range 28	County Eddy
Drilling Contractor Capstar		Type of Equipment Rotary			
<u>APPROVED CASING PROGRAM</u>					
<i>* Witness</i>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
12 1/4	<i>* 8 5/8</i>	24#		500'	150-200
7 7/8	5 1/2	15.5#		2200'	150
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole <u>12 1/4"</u> Size of Casing <u>8 5/8"</u> Sacks cement required _____					
Type of Shoe used <u>guide</u> Float collar used <u>17501T</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>370'</u> Set <u>370'</u> Feet of <u>8 5/8"</u> Inch <u>34</u> # Grade <u>5-55</u>					
<u>(New)</u> used csg. @ <u>370'</u> with <u>300 220s</u> sacks neat cement around shoe					
+ _____ sax _____ additives _____					
Plug down @ <u>9:00</u> (AM) (PM) Date <u>OCT, 20 - 92</u>					
Cement circulated <u>yes</u> No. of Sacks <u>255x</u>					
Cemented by <u>Halliburton</u> Witnessed by <u>M.S.</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					
T. SALT 410' EST.					
Last drly b/c 10 306'					