

7. ANCILLARY FACILITIES:

A. None required.

8. WELLSITE LAYOUT:

A. Exhibit "C" shows the relative location and dimensions of the well pad, mud pits, reserve pits, trash container and location of major rig components.

B. A 400' X 400' area has been flagged surrounding the staked well.

9. PLANS AND RESTORATION OF THE SURFACE:

A. After completion of drilling and/or completion operations, all equipment not needed for producing operations will be removed. Pits will be filled in after all fluids have evaporated and the location cleaned of all trash and junk to leave the wellsite in an aesthetically pleasing condition as reasonably possible. All production facilities left on location will be painted to conform with BLM painting regulations within 120 days of completion.

10. OTHER INFORMATION:

A. The geologic surface formation is hard clay interspersed with sand and chert outcroppings. Vegetative covering is generally sparse except in low-lying areas where grass is prevalent. Other vegetative covering consists mostly of greasewood and bear grass.

B. The estimated tops of geologic markers are as follows:

Queen	1260'	Cisco	7740'
✓ San Andres	2100'	Canyon	8350'
Glorieta	3720'	Strawn	8900'
✓ Tubb	4930'	Atoka	9500'
✓ Abo	5900'	✓ Morrow	9600'
✓ Wolfcamp	6900'	Miss.	10,100'