

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 30-015-27448
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VB-414
7. Lease Name or Unit Agreement Name Beauregard ANM State Com
8. Well No. 1
9. Pool name or Wildcat Red Lake East Upper Penn
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3475' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	AUG 25 1993
2. Name of Operator YATES PETROLEUM CORPORATION	C.I.D.
3. Address of Operator 105 South 4th St., Artesia, NM 88210	
4. Well Location Unit Letter L : 1980 Feet From The South Line and 660 Feet From The West Line Section 14 Township 18S Range 27E NMPM Eddy County	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Intermediate casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 2190'. Ran 49 joints of 9-5/8" 36# J-55 ST&C (2202.35') of casing set at 2190'. 1-Texas Pattern notched guide shoe set at 2190'. Float collar set at 2142.37'. Cemented with 650 sacks Pacesetter Lite, 1/4#/sack celloseal and 2% CaCl2 (yield 2.0, weight 12.4). Tailed in with 200 sacks Class "C" 2% CaCl2 (yield 1.32, weight 14.8). PD 6:00 AM 8-1-93. Bumped plug to 900 psi, OK. Circulated 130 sacks. WOC. Drilled out at 12:30 PM 8-2-93. WOC 18 hours and 30 minutes. Nippled up and tested to 1000# for 30 minutes, OK. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE Aug. 24, 1993
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

SEP 7 1993

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: