

clsr
17

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

JUL 19 1993

WELL API NO. 30-015-27461
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Vandiver AIM
8. Well No. 2
9. Pool name or Wildcat West Atoka Morrow
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3387'

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210
4. Well Location Unit Letter <u>G</u> : <u>2091</u> Feet From The <u>North</u> Line and <u>1763</u> Feet From The <u>East</u> Line Section <u>17</u> Township <u>18S</u> Range <u>26E</u> NMPM <u>Eddy</u> County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3387'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Resume drilling, surface casing & cmt <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole at 3:30 PM 6-19-93. Set 40' of 20" conductor. Cemented to surface.
Resumed drilling a 17-1/2" hole at 2:00 AM 7-1-93.

TD 510'. Ran 13 joints of 13-3/8" 54.5# J-55 (513.25') of casing set at 510'. 1-Texas Pattern notched guide shoe set at 510'. Insert float set at 472'. Cemented with 325 sacks Pacesetter Lite "C", 5#/sack gilsonite, 1/4#/sack celloseal and 3% CaCl2 (yield 1.98, weight 12.4). Tailed in with 200 sacks "C" 2% CaCl2 (yield 1.32, weight 14.8). PD 1:15 AM 7-1-93. Bumped plug to 500 psi, OK. Circulated 68 sacks cement. WOC. Drilled out at 8:15 AM 7-2-93. WOC 31 hours. Nipped up and tested to 500 psi for 15 minutes. Reduced hole to 12-1/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE July 12, 1993
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS

JUL 20 1993

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: