

District Office

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-27461

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER ☐ **OCT 15 1993**

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter G : 2091 Feet From The North Line and 1763 Feet From The East Line

Section 17 Township 18S Range 26E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3387'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Production casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 9090'. Ran 220 joints of 5-1/2" 17# & 15.5# casing as follows: 14 joints of 5-1/2" 17# (568.22'); 44 joints of 5-1/2" 17# (1812.73'); 121 joints of 5-1/2" 15.5# (5023.02') and 41 joints of 5-1/2" 17# (1700.99') (Total 9108.41') of casing set at 9090'. Float shoe set at 9090'. Float collar set at 9045.74'. DV tool set at 6051'. Cemented in two stages as follows: Stage 1: 500 sacks Class "H", 8#/sack CSE, 5#/sack gilsonite, .6% CF-14 and .35% Thrifty Lite (yield 1.75, weight 13.6). PD 10:00 PM 7-24-93. Bumped plug to 1150 psi for 5 minutes. Stage 2: 1050 sacks PSL, 5#/sack gilsonite, 5#/sack salt, 1/4#/sack cello-seal and .4% CF-14 (yield 1.18, weight 15.6). Tailed in with 100 sacks Class "H" (yield 1.18, weight 15.6). PD 4:00 AM 4-25-93. Bumped plug to 3750 psi for 5 minutes, OK. Released rig at 8:00 AM 7-25-93. NOTE: Proceeded 1st stage of cement with 500 gallons WMW-1 and 500 gallons Surebond.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE Oct. 14, 1993

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE OCT 29 1993

CONDITIONS OF APPROVAL, IF ANY: