

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTNM OIL & GAS COMMISSION
Drawer DD
Artesia, NM 88210FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 2310' FEL of Section 5-T18S-R27E

5. Lease Designation and Serial No.

NM-71762

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Choque AMX Federal #1

9. API Well No.

30-015-27521

10. Field and Pool, or Exploratory Area

Yeso Wildcat

11. County or Parish, State

Eddy County, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☒ Other Resumed drilling; surf.
casing & cement☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Resumed drilling a 12-1/4" hole with rotary tools at 10:00 AM 8-10-93. NOTE: Notified Duncan Whitlock with BLM in Carlsbad.

TD 1350'. Ran 31 joints of 8-5/8" 24# J-55 (1353') of casing set at 1350'. 1-Texas Pattern notched guide shoe set at 1350'. Float collar set at 1305'. Cemented with 450 sacks Pacesetter Lite "C", 10#/sack gilsonite, 1/2#/sack celloseal and 3% CaCl₂ (yield 1.32, weight 14.8). PD 8:00 AM 8-13-93. Bumped plug to 750 psi, OK. Cement did not circulate. WOC 4 hours. Ran 1". Tagged cement at 47'. Spot 50 sacks cement. PD 1:45 PM 8-13-93. Circulated 5 sacks to pit. WOC. Drilled out at 2:45 AM 8-14-93. WOC 18 hours and 45 minutes. Nippled up and tested to 1500# for 30 minutes, OK. Reduced hole to 7-7/8". Resumed drilling.

ACCEPTED FOR RECORD

OCT 12 1993

CARLSBAD, NEW MEXICO

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Clerk

Date Sept. 16, 1993

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: