

RECEIVED
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-71762

6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 2310' FEL of Section 5-T18S-R27E

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Choque AMX Federal #1

9. API Well No.

30-015-27521

10. Field and Pool, or Exploratory Area

Yeso Wildcat

11. County or Parish, State

Eddy County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Perfs & acid

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in and rigged up pulling unit. WIH w/bit and scraper. Drilled DV tool at 1718'. Tested casing to 3000#. Displaced hole with 2% KCL water. POOH. WIH and perforated Yeso (Y1) 3462-3510' w/9 .42" holes as follows: 3462, 74, 78, 83, 87, 94, 96, 3502' and 3510'. Straddled perforations 3462-3510'. Acidized perfs. 3462-3510' w/2000 gallons 20% NEFE HCL acid and ball sealers. WIH and perforated 2903-2916' (Y3) w/16 .42" holes (2 SPF) as follows: 2903, 04, 08, 09, 13, 14, 15 & 2916'. Straddled perforations 2903-2916' and acidized with 2000 gallons 20% NEFE HCL acid and ball sealers. Swabbing. Moved RBP and packer. Straddled perforations 3462-3510' (Y-1) and swabbed. WIH and perforated 2744-2770' (Y-4) w/9 .42" holes as follows: 2744, 49, 50, 51, 55, 56, 62, 63 & 2770'. WIH w/packer and RBP. Straddled perforations 2744-2770' and acidized with 2000 gallons 20% NEFE HCL acid and ball sealers. Swabbing. POOH w/packer. Set CIBP at 2715' with 35' of cement on top. Perforated 2 holes at 2200' and 2 holes at 1850'. WIH w/packer. Set above perforations at 2200'. Pumped 100 bbls of fresh water. POOH with packer. WIH w/retainer on 2-7/8" tubing. Set at 2150'. Established circulation. Cemented with 125 sacks Premium Plus. Pulled out of retainer. Pulled up to 1750'. Reversed to surface. Shut well in. WIH and perforated 1822-1947' w/18 .42" holes as follows: 1822, 23, 28, 29, 32, 33, 59, 64, 74, 78, 83, 99, 1905, 14, 28, 40, 43 & 1947'.

CONTINUED

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Clerk

Date Sept. 16, 1993

(This space for Federal or State office use)

Approved by
Conditions of approval, if any:

Title

ACCEPTED FOR RECORD

J. Lara
OCT 12 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

CARLSBAD, NEW MEXICO