Form 3160-5 (June 1990)

## UNIT STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OIL CONSERVATION DIV 811 S. 1st ST. ARTESIA, NM 88210-2834 FORM APPROVED Budget Bureau No. 1004-0135

Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS		5. Lease Designation and Serial No.
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals		LC 026874-A
		6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE  1. Type of Well		NA
		7. If Unit or CA, Agreement Designation
Oil Gas Other Well Other		West Red Lake
<ol> <li>Name of Operator         DEVON ENERGY CORPORATION (NEVADA)</li> <li>Address and Telephone No.         20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611</li> <li>Location of Well (Footage. Sec., T., R., M., or Survey Description)         280' FSL and 850' FEL of Section 6-18S-XE, Unit letter "P"         27 E</li> </ol>		8. Well Name and No.
		West Red Lake #57
		9. API Well No.
		30-015-28539
		10. Field and Pool, or Exploratory Area
		Red Lake Q-GB-SA
		11. County or Parish, State
		Eddy County, NM
CHECK APPROPRIATE BOX(s	S) TO INDICATE NATURE OF NOTICE, REP	ORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
ra .	Casing Repair	Water Shut-Off Conversion to Injection
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other Spud, TD & csg strings	Dispose Water (Note: Report results of multiple completion on Well
13. Describe Proposed or Completed Operations (Clearly state all se	ertinent details, and give pertinent dates, including estimated date of starting any	Completion or Recompletion Report and Log form
locations and measured and true vertical depths for all market	rs and zones pertinent to this work.)*	proposed work. If well is directionally drilled, give subsurface
Spud on 10/13/95 @ 1430 hrs, Drld 1	12 1/4" hala ta 1000	
On 10/15/95, Ran 25 jts of 8-5/8" 24#	<sup>‡</sup> J-55 8rd LT&C, shoe set @ 999'. (FC @ 93	5', 4 centralizers)
Halliburton Cmt'd as follows: Lead	w/300 sxs Hall lite (w/2% CaCl2 + 1/4 pps flo	PER ENVERDA plus
"C" (w/2% CaCl2 + 1/4 pps flocele)	90 sxs cmt returned to surface	The Board of the plans
Drld 7-7/8" hole. Reached TD of 215	0' on 10/17/95 @ 1115 hrs.	DEC 1 8 1995
Schlumber Ran GR/CNL/LDT and GR	/DFF/MSFL logs	
	-55 8rd LT&C csg, shoe set @ 2149' (FC @ 2	OIL CON. DIV.
	v/150 Hall lite prem plus (5 pps salt, 1/4 pps fl	ocele) Tail w/275 ava promining
"C" (w/3 pps KCL) 70 sxs cmt return	ned to surface	occie) Tan w/2/3 sxs prem plus
	10	
Released Rig @ 1700 hrs 10/18/95. W	OCU.	
14. I hereby certify that the foregoing is true and correct		1995
Minne (no 1/	Diana Keys	13/1/2
Signed AND ON THE	Title Engineering Technician	
This space for Federal or State office use)		
Approved by	Title	Date
Conditions of approval, if any:		

