

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN THE
(Other Instructions
reverse side)

CATE
OR TO

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-025503

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

B.S.W.U.

9. WELL NO.

#7

10. FIELD AND POOL, OR WILDCAT

Shugart-Yates-(SR-Q-GR)

11. SEC., T., R., M., OR BLK. AND
SUBDIVISION OR AREA

Sec.26,T.18S, R.30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Hanson Operating Company, Inc.

3. ADDRESS OF OPERATOR

P.O. Box 1515, Roswell, New Mexico 88202-1515

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

Unit I, NE 1/4 SE 1/4, 1530' FSL & 940' FEL

14. PERMIT NO.

30-015-27546

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3446.2' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANT

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Spud & Csg Job

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/31/93 Spud well at 4:00 PM 7/31/93.

8/2/93 Ran & cemented 17 jt 8 5/8" 24# ST&C casing as follows:
Guide shoe, 1 jt 8 5/8" csg(41.39'). Insert float collar
&(716.61') 8 5/8" csg. Set @758'.

Cement As Follows:

500 sx Premium Plus w/2% Cacl. Plug dn @12:00 8/2/93.

Did not cement to surface. Rig up & ran Temp Survey. Found cement
@235', notified BLM. Ran 1" down to 235' and tagged cement. Set

at 35 sx Premium Plus w/3% Cacl plug at 5:21 AM.

6:41 AM - Tagged cement top at 235'. Set at 35 sx Premium Plus w/3% Cacl Plug

8:00 AM - Tagged cement at 235'. Set a 35 sx Premium Plus plug w/3% Cacl.

10:00 AM - Tagged cement at 231'. Poured 5 yd of 3/8 Pea Gravel. Tagged
Pea Gravel at 216'. Set at 35 sx Premium Plus w/3% Cacl plug. 12:30 AM -
Tagged at 106'. Set a 75 sx Premium Plus Plug w/3% Cacl.

Circulated 10 sx to surface pit.

18. I hereby certify that the foregoing is true and correct

SIGNED

Catharina A. McShaw

TITLE Production Analyst

DATE August 11, 1993

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side