

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

RECEIVED

AUG 25 1993

| |
|---|
| WELL API NO. 30-015-27555 |
| 5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No. E-7811 |
| 7. Lease Name or Unit Agreement Name Cedar Breaks "2" State |
| 8. Well No. 4 |
| 9. Pool name or Wildcat Walters Lake Bone Spring |
| 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3515' GR |

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK OR
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

| | |
|---|---|
| 1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | 2. Name of Operator Newbourne Oil Company |
| 3. Address of Operator P.O. Box 5270 Hobbs, New Mexico 88241 | 4. Well Location Unit Letter <u>0</u> : <u>2310</u> Feet From The <u>East</u> Line and <u>330</u> Feet From The <u>South</u> Line Section <u>2</u> Township <u>18S</u> Range <u>2E</u> <u>30</u> NMPM Eddy County |

| | |
|---|--|
| 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data | |
| NOTICE OF INTENTION TO: | SUBSEQUENT REPORT OF: |
| PERFORM REMEDIAL WORK <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> |
| OTHER: <input type="checkbox"/> | PLUG AND ABANDONMENT <input type="checkbox"/> |
| | <input checked="" type="checkbox"/> CEMENT JOB |
| | OTHER: <input type="checkbox"/> |

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

08/21/93 Drilled 8-3/4" production hole to a depth of 7425' KB. Ran electric logs. Ran 181 jts. of used 5-1/2", 23#, N-80, 8rd, LT&C casing and set @ 7425' KB. Halliburton cemented w/1450 sks. of Howco Lite "C" containing 3#/sk. Gilsonite + 1/4#/sk. Flocele + 2 1/2#/sk. salt followed by 375 sks. of Class "C" containing 1.3#/sk. KCL + .4% Halad-9 + .3% CFR-3 + 5#/sk. fumed silica. Plug down to 7385' @ 6:45 a.m. 08/23/93. Circulated 140 sacks to pit. Set slips and released rig @ 3:00 p.m. 08/23/93.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bill Pierce TITLE Drlg. Supt. DATE 08/24/93
(505)
TELEPHONE NO. 393-5905

TYPE OR PRINT NAME Bill Pierce

(This space for State Use) ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II
APPROVED BY _____ TITLE _____ DATE SEP 7 1993

CONDITIONS OF APPROVAL, IF ANY:

08 1

[illegible]