

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

DEC 08 1993

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FNL & 1650' FWL of Section 11-T18S-R30E

5. Lease Designation and Serial No.

NM-28099

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Pennzoil MZ Fed. #2

9. API Well No.

30-015-27591

10. Field and Pool, or Exploratory Area

Walters Lake Bone Springs

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐
- Notice of Intent
-
- ☒
- Subsequent Report
-
- ☐
- Final Abandonment Notice

TYPE OF ACTION

- ☐
- Abandonment
-
- ☐
- Recompletion
-
- ☐
- Plugging Back
-
- ☐
- Casing Repair
-
- ☐
- Altering Casing
-
- ☒
- Other
- Spud, surface csg & cement
-
- ☐
- Change of Plans
-
- ☐
- New Construction
-
- ☐
- Non-Routine Fracturing
-
- ☐
- Water Shut-Off
-
- ☐
- Conversion to Injection
-
- ☐
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 26" hole at 1:00 PM 8-22-93. Drilled to 40'. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified Leta with the BLM Answering Service of spud. Resumed drilling a 17-1/2" hole with rotary tools on 8-24-93.

TD 582'. Ran 13 joints of 13-3/8" 54.5# J-55 (587.74') of casing set at 582'. 1-Texas Pattern notched guide shoe set at 582'. Insert float set at 539.07'. Cemented with 200 sacks "H", 12% Thixad, 1/2#/sack celloseal, 10#/sack gilsonite and 2% CaCl₂ (yield 1.54, weight 14.5) and 450 sacks Pacesetter Lite "C", 1/4#/sack celloseal, 5#/sack gilsonite and 3% CaCl₂ (yield 1.95, weight 12.6). Tailed in with 200 sacks "C" and 2% CaCl₂ (yield 1.32, weight 14.8). PD 7:15 AM 8-25-93. Bumped plug to 500 psi, OK. Circulated 120 sacks. WOC. Drilled out at 7:45 AM 8-26-93. WOC 24 hours and 30 minutes. Nipped up and tested to 3000# for 10 minutes, OK. Reduced hole to 12-1/4". Resumed drilling.

ACCEPTED FOR RECORD

(ONIG. SGD.) DAVID R. GLASS
JUL 7 1993

CARLSBAD, NEW MEXICO

14. I hereby certify that the foregoing is true and correct

Signed Kusty KleinTitle Production ClerkDate Sept. 16, 1993

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side