				1. A.
2160.5		STATES		FORM APPROVED
m 3160-5 ne 1990)	DEPARTMENT O		<u>l</u> etuwat tu mu anternationationationationationationationatio	Budget Bureau No. 1004-0135 Expires: March 31, 1993
	BUREAU OF LAN		NEDEIVEN	5. Lease Designation and Serial No.
				NM-28099
SUI	NDRY NOTICES AN	D REPORTS QN WI	ELLS	6. If Indian, Allottee or Tribe Name
o not use this form fo Use "	or proposals to drill or APPLICATION FOR PE	r to deepen or ree ntry ERMIT—" for such pr	y to a different reserve	pir.
	SUBMIT IN			7. If Unit or CA, Agreement Designation
Type of Well		<u> </u>	· · · ·	
X Oil Gas Well	Other	· · · · · · · · · · · · · · · · · · ·	·	8. Well Name and No.
Name of Operator		(505)	7/0 1/71)	Pennzoil MZ Fed. #2
YATES PETROLEUM	CORPORATION	(505)	748-1471)	30-015-27591
Address and Telephone No.	St., Artesia, NM	88210	× 4000	10. Field and Pool, or Exploratory Area
Location of Well (Footage, Sec	., T., R., M., or Survey Descrip	tion)	<u>NOA 0 8 1889</u>	Walters Lake Bone Spring
	' FWL of Section		C. L. D	11. County or Parish, State
	norre Anglis prins i Colo el 1944. Norre		Water of the Water	
· · · · · · · · · · · · · · · · · · ·			·	Eddy Co., NM
CHECK APP	ROPRIATE BOX(s) T	O INDICATE NATU	JRE OF NOTICE, RE	PORT, OR OTHER DATA
TYPE OF SUB	MISSION		TYPE OF ACT	ION
Notice of Inten		Abandonme	ent	Change of Plans
		Recompleti	ion	New Construction
X Subsequent Rep	port	Plugging B	Back	Non-Routine Fracturing
F			-	Water Shut-Off
Final Abandon	ament Notice		Casing	Conversion to Injection
			ntermediate cso &	Cmt Dispose Water
		▲ Other	ntermediate csg &	(Note: Report results of multiple completion on Well
				(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
give subsurface locations a	and measured and true vertical de	tinent details, and give pertinent of the pertinent of th	dates, including estimated date of s pertinent to this work.)*	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled
give subsurface locations a TD 1667'. Ran Pattern notche packer stage c "H" with 1% TF weight 16.5). Stage 2: 250 Circulated 95	and measured and true vertical de and measured and true vertical de and guide shoe set collar set at 488 F-4 (yield .89, we PD 2:20 AM 8-28 sacks "H" and 1%	tinent details, and give pertinent epths for all markers and zones 5/8" 36# J-55 (1 at 1667'. 2 fl '. Cemented in eight 18.0) and -93. Bumped plu CaCl2 (yield 1. illed out at 11:	dates, including estimated date of s pertinent to this work.)* 670.29') of casin oat collars set a 2 stages as follo 200 sacks "H" and g to 1500 psi. (06, weight 16.5) 30 AM 8-29-93. 1	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled at 1570.49'. Davis Lynch bws: Stage 1: 1000 sacks d 1% CaCl2 (yield 1.06, Circulated 115 sacks. . PD 3:15 AM 8-28-93. Nippled up and tested to
give subsurface locations a TD 1667'. Ran Pattern notche packer stage c "H" with 1% TF weight 16.5). Stage 2: 250 Circulated 95	and measured and true vertical de and measured and true vertical de ed guide shoe set collar set at 488 F-4 (yield .89, we PD 2:20 AM 8-28 sacks "H" and 1% sacks. WOC. Dr	tinent details, and give pertinent epths for all markers and zones 5/8" 36# J-55 (1 at 1667'. 2 fl '. Cemented in eight 18.0) and -93. Bumped plu CaCl2 (yield 1. illed out at 11:	dates, including estimated date of s pertinent to this work.)* 670.29') of casin oat collars set a 2 stages as follo 200 sacks "H" and g to 1500 psi. (06, weight 16.5) 30 AM 8-29-93. N 8-3/4". Resumed	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled ing set at 1667'. 1-Texas at 1570.49'. Davis Lynch bws: Stage 1: 1000 sacks d 1% CaCl2 (yield 1.06, Circulated 115 sacks. . PD 3:15 AM 8-28-93. Nippled up and tested to drilling.
give subsurface locations a TD 1667'. Ran Pattern notche packer stage c "H" with 1% TF weight 16.5). Stage 2: 250 Circulated 95	and measured and true vertical de and measured and true vertical de ed guide shoe set collar set at 488 F-4 (yield .89, we PD 2:20 AM 8-28 sacks "H" and 1% sacks. WOC. Dr	tinent details, and give pertinent epths for all markers and zones 5/8" 36# J-55 (1 at 1667'. 2 fl '. Cemented in eight 18.0) and -93. Bumped plu CaCl2 (yield 1. illed out at 11:	dates, including estimated date of s pertinent to this work.)* 670.29') of casin oat collars set a 2 stages as follo 200 sacks "H" and g to 1500 psi. (06, weight 16.5) 30 AM 8-29-93. 1	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled ing set at 1667'. 1-Texas at 1570.49'. Davis Lynch bws: Stage 1: 1000 sacks d 1% CaCl2 (yield 1.06, Circulated 115 sacks. . PD 3:15 AM 8-28-93. Nippled up and tested to drilling.
give subsurface locations a TD 1667'. Ran Pattern notche packer stage c "H" with 1% TF weight 16.5). Stage 2: 250 Circulated 95	and measured and true vertical de and measured and true vertical de ed guide shoe set collar set at 488 F-4 (yield .89, we PD 2:20 AM 8-28 sacks "H" and 1% sacks. WOC. Dr	tinent details, and give pertinent epths for all markers and zones 5/8" 36# J-55 (1 at 1667'. 2 fl '. Cemented in eight 18.0) and -93. Bumped plu CaCl2 (yield 1. illed out at 11:	dates, including estimated date of s pertinent to this work.)* 670.29') of casin oat collars set a 2 stages as follo 200 sacks "H" and g to 1500 psi. (06, weight 16.5) 30 AM 8-29-93. N 8-3/4". Resumed	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled at 1570.49'. Davis Lynch bws: Stage 1: 1000 sacks d 1% CaCl2 (yield 1.06, Circulated 115 sacks. . PD 3:15 AM 8-28-93. Nippled up and tested to drilling.
give subsurface locations a TD 1667'. Ran Pattern notche packer stage c "H" with 1% TF weight 16.5). Stage 2: 250 Circulated 95	and measured and true vertical de and measured and true vertical de ed guide shoe set collar set at 488 F-4 (yield .89, we PD 2:20 AM 8-28 sacks "H" and 1% sacks. WOC. Dr	tinent details, and give pertinent epths for all markers and zones 5/8" 36# J-55 (1 at 1667'. 2 fl '. Cemented in eight 18.0) and -93. Bumped plu CaCl2 (yield 1. illed out at 11:	dates, including estimated date of s pertinent to this work.)* 670.29') of casin oat collars set a 2 stages as follo 200 sacks "H" and g to 1500 psi. (06, weight 16.5) 30 AM 8-29-93. N 8-3/4". Resumed	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled at 1570.49'. Davis Lynch ows: Stage 1: 1000 sacks d 1% CaCl2 (yield 1.06, Circulated 115 sacks. . PD 3:15 AM 8-28-93. Nippled up and tested to drilling. OR RECORD DAVID L GLASS
give subsurface locations a TD 1667'. Ran Pattern notche packer stage c "H" with 1% TF weight 16.5). Stage 2: 250 Circulated 95	and measured and true vertical de and measured and true vertical de ed guide shoe set collar set at 488 F-4 (yield .89, we PD 2:20 AM 8-28 sacks "H" and 1% sacks. WOC. Dr	tinent details, and give pertinent epths for all markers and zones 5/8" 36# J-55 (1 at 1667'. 2 fl '. Cemented in eight 18.0) and -93. Bumped plu CaCl2 (yield 1. illed out at 11:	dates, including estimated date of s pertinent to this work.)* 670.29') of casin oat collars set a 2 stages as follo 200 sacks "H" and g to 1500 psi. (06, weight 16.5) 30 AM 8-29-93. N 8-3/4". Resumed	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled at 1570.49'. Davis Lynch bws: Stage 1: 1000 sacks d 1% CaCl2 (yield 1.06, Circulated 115 sacks. . PD 3:15 AM 8-28-93. Nippled up and tested to drilling.
give subsurface locations a TD 1667'. Ran Pattern notche packer stage c "H" with 1% TF weight 16.5). Stage 2: 250 Circulated 95	and measured and true vertical de and measured and true vertical de ed guide shoe set collar set at 488 F-4 (yield .89, we PD 2:20 AM 8-28 sacks "H" and 1% sacks. WOC. Dr	tinent details, and give pertinent epths for all markers and zones 5/8" 36# J-55 (1 at 1667'. 2 fl '. Cemented in eight 18.0) and -93. Bumped plu CaCl2 (yield 1. illed out at 11:	dates, including estimated date of s pertinent to this work.)* 670.29') of casin oat collars set a 2 stages as follo 200 sacks "H" and g to 1500 psi. (06, weight 16.5) 30 AM 8-29-93. M 8-3/4". Resumed ACCEPTED F((ORIG. SGD.)	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled ing set at 1667'. 1-Texas at 1570.49'. Davis Lynch bws: Stage 1: 1000 sacks d 1% CaCl2 (yield 1.06, Circulated 115 sacks. . PD 3:15 AM 8-28-93. Nippled up and tested to drilling. OR RECORD DAVID - GLASS
give subsurface locations a TD 1667'. Ran Pattern notche packer stage c "H" with 1% TF weight 16.5). Stage 2: 250 Circulated 95	and measured and true vertical de and measured and true vertical de ed guide shoe set collar set at 488 F-4 (yield .89, we PD 2:20 AM 8-28 sacks "H" and 1% sacks. WOC. Dr	tinent details, and give pertinent epths for all markers and zones 5/8" 36# J-55 (1 at 1667'. 2 fl '. Cemented in eight 18.0) and -93. Bumped plu CaCl2 (yield 1. illed out at 11:	dates, including estimated date of s pertinent to this work.)* 670.29') of casin oat collars set a 2 stages as follo 200 sacks "H" and g to 1500 psi. (06, weight 16.5) 30 AM 8-29-93. M 8-3/4". Resumed ACCEPTED F((ORIG. SGD.)	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled at 1570.49'. Davis Lynch ows: Stage 1: 1000 sacks d 1% CaCl2 (yield 1.06, Circulated 115 sacks. . PD 3:15 AM 8-28-93. Nippled up and tested to drilling. OR RECORD DAVID L GLASS
give subsurface locations a TD 1667'. Ran Pattern notche packer stage c "H" with 1% TF weight 16.5). Stage 2: 250 Circulated 95 3000 psi for 1	and measured and true vertical de and measured and true vertical de ed guide shoe set collar set at 488 F-4 (yield .89, we PD 2:20 AM 8-28- sacks "H" and 1% sacks. WOC. Dr 10 minutes, OK.	tinent details, and give pertinent epths for all markers and zones 5/8" 36# J-55 (1 at 1667'. 2 fl '. Cemented in eight 18.0) and -93. Bumped plu CaCl2 (yield 1. illed out at 11:	dates, including estimated date of s pertinent to this work.)* 670.29') of casin oat collars set a 2 stages as follo 200 sacks "H" and g to 1500 psi. (06, weight 16.5) 30 AM 8-29-93. M 8-3/4". Resumed ACCEPTED F((ORIG. SGD.)	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled ing set at 1667'. 1-Texas at 1570.49'. Davis Lynch bws: Stage 1: 1000 sacks d 1% CaCl2 (yield 1.06, Circulated 115 sacks. . PD 3:15 AM 8-28-93. Nippled up and tested to drilling. OR RECORD DAVID - GLASS
give subsurface locations a TD 1667'. Ran Pattern notche packer stage c "H" with 1% TF weight 16.5). Stage 2: 250 Circulated 95 3000 psi for 1	and measured and true vertical de and measured and true vertical de ed guide shoe set collar set at 488 F-4 (yield .89, we PD 2:20 AM 8-28- sacks "H" and 1% sacks. WOC. Dr 10 minutes, OK.	tinent details, and give pertinent of spths for all markers and zones 5/8" 36# J-55 (1 at 1667'. 2 fl '. Cemented in eight 18.0) and -93. Bumped plu CaCl2 (yield 1. illed out at 11: Reduced hole to	dates, including estimated date of s pertinent to this work.)* 670.29') of casin oat collars set a 2 stages as follo 200 sacks "H" and g to 1500 psi. (06, weight 16.5) 30 AM 8-29-93. M 8-3/4". Resumed ACCEPTED F((ORIG. SGD.)	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled ing set at 1667'. 1-Texas at 1570.49'. Davis Lynch bws: Stage 1: 1000 sacks d 1% CaCl2 (yield 1.06, Circulated 115 sacks. . PD 3:15 AM 8-28-93. Nippled up and tested to drilling. OR RECORD DAVID - GLASS
give subsurface locations a TD 1667'. Ran Pattern notche packer stage c "H" with 1% TF weight 16.5). Stage 2: 250 Circulated 95 3000 psi for 1	and measured and true vertical de and measured and true vertical de and guide shoe set collar set at 488 7-4 (yield .89, we PD 2:20 AM 8-28 sacks "H" and 1% sacks. WOC. Dr 10 minutes, OK. D going 15 true and correct	tinent details, and give pertinent of spths for all markers and zones 5/8" 36# J-55 (1 at 1667'. 2 fl '. Cemented in eight 18.0) and -93. Bumped plu CaC12 (yield 1. illed out at 11: Reduced hole to	dates, including estimated date of s pertinent to this work.)* 670.29') of casin oat collars set a 2 stages as follo 200 sacks "H" and g to 1500 psi. (06, weight 16.5). 30 AM 8-29-93. N 8-3/4". Resumed ACCEPTED F((ORIG. SGD.)	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled ing set at 1667'. 1-Texas at 1570.49'. Davis Lynch bws: Stage 1: 1000 sacks d 1% CaCl2 (yield 1.06, Circulated 115 sacks. . PD 3:15 AM 8-28-93. Nippled up and tested to drilling. OR RECORD DAVID GLASS EW MEXICO
give subsurface locations a TD 1667'. Ran Pattern notche packer stage c "H" with 1% TF weight 16.5). Stage 2: 250 Circulated 95 3000 psi for 1 1 hereby ceptor that the foreg Signed <u>Ustry</u> (This space for Federal or Sta	and measured and true vertical de and measured and true vertical de and guide shoe set collar set at 488 F-4 (yield .89, we PD 2:20 AM 8-28 sacks "H" and 1% sacks. WOC. Dr: 10 minutes, OK. 19 going is true and correct Line office use)	tinent details, and give pertinent of spths for all markers and zones 5/8" 36# J-55 (1 at 1667'. 2 fl '. Cemented in eight 18.0) and -93. Bumped plu CaC12 (yield 1. illed out at 11: Reduced hole to	dates, including estimated date of s pertinent to this work.)* 670.29') of casin oat collars set a 2 stages as follo 200 sacks "H" and g to 1500 psi. (06, weight 16.5). 30 AM 8-29-93. N 8-3/4". Resumed ACCEPTED F((ORIG. SGD.)	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled ing set at 1667'. 1-Texas at 1570.49'. Davis Lynch bws: Stage 1: 1000 sacks d 1% CaCl2 (yield 1.06, Circulated 115 sacks. . PD 3:15 AM 8-28-93. Nippled up and tested to drilling. OR RECORD DAVID GLASS EW MEXICO
give subsurface locations a TD 1667'. Ran Pattern notche packer stage c "H" with 1% TF weight 16.5). Stage 2: 250 Circulated 95 3000 psi for 1 1 hereby ceptify that the foreg Signed Musture	and measured and true vertical de and measured and true vertical de and guide shoe set collar set at 488 F-4 (yield .89, we PD 2:20 AM 8-28 sacks "H" and 1% sacks. WOC. Dr: 10 minutes, OK. 19 going is true and correct Line office use)	tinent details, and give pertinent of spths for all markers and zones 5/8" 36# J-55 (1 at 1667'. 2 fl. '. Cemented in eight 18.0) and -93. Bumped plu CaC12 (yield 1. illed out at 11: Reduced hole to 	dates, including estimated date of s pertinent to this work.)* 670.29') of casin oat collars set a 2 stages as follo 200 sacks "H" and g to 1500 psi. (06, weight 16.5). 30 AM 8-29-93. N 8-3/4". Resumed ACCEPTED F((ORIG. SGD.)	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) starting any proposed work. If well is directionally drilled ing set at 1667'. 1-Texas at 1570.49'. Davis Lynch ows: Stage 1: 1000 sacks in 1% CaCl2 (yield 1.06, Circulated 115 sacks. . PD 3:15 AM 8-28-93. Nippled up and tested to drilling. OR RECORD DAVID - GLASS EW MEXICO