Interest certuly that the according the top unit allowable for the pool in which well is located by more than 25 percent. Operator is encouraged to take advantage of this 25 percent tolerance in Gas volumes must be reported in MCF measured at a pressure base of 15.025 psia and a temperature of 60° F.	PIPELINE	Pennzoil MS Federal 2 C 11 18 30 11-18-93 F 28/64" 320 M 24 211 43 270 56	U S T R TEST 5 SIZE PRESS ABLE HOURS BBLS. OIL BBLS.	HOKE TBG DAILY LENGTH PROD. DURING TEST	TES PETROLEUM CORPORATION Walters Lake Bone Springs Eddy	GAS - OIL RATIO TEST	10 Santa Fe, New Mexico 8/304-2088	P.O. Drawer DD, Artesia, NM 88210 P.O. Drawer DD, Artesia, NM 88210	0, HODDS, NM 88240 OIL CONSERVATION DIVISION NOV 1 9 7993	ies to Appropriate Energy, Minerals and Natural Resources Department
nowledge and belief. <u> <i>w</i> & U.7.1</u> – P <u>roduction Supvr</u> .	CONNECTION ELINE 11-17-9	 270 560 2074	BBLS MC.F. CU.FT/BBL							Form C-116 Revised 1/1/89

•