


DRILLING CONTROL
CONDITION IV-B-5000 PSI WP



DRILLING CONTROL
MATERIAL LIST - CONDITION IV - B

- A Texaco Wellhead
- B 5000# W.P. drilling spool with a minimum 2" flanged outlet for kill line and 3" minimum flanged outlet for choke line.
- C 5000# W.P. Dual ram type preventer, hydraulic operated with 1" steel, 5000# W.P. control lines.
- D 5000# W.P. Annular preventer, hydraulic operated with 1" steel, 3000# W.P. control lines.
- E Rotating Head with fill up outlet and extended Blosse line.
- 1,2,4,5, 2" minimum 5000# W.P. flanged full opening steel gate valve, or Halliburton Lo Torc Plug valve.
- 8,10,11, 2"
- 12 2" minimum 5000# W.P. back pressure valve.
- 3 2" minimum 5000# W.P. flanged full opening steel gate valve, or Halliburton Lo Torc Plug valve.
- 6,9 3" minimum 5000# W.P. flanged hydraulic valve
- 7 3" minimum Schedule 160, Grade B, seamless line pipe
- 15 2" minimum x 3" 5000# W.P. flanged cross
- 16 2" minimum 5000# W.P. adjustable chokes with carbide trim.
- 13,14 Cameron Mud Gauge or equivalent (location in choke line optional).
- 17 6" minimum 1000# hydraulic flanged valve.
- 18 8" minimum steel flow line.
- 24 2" minimum 3000# W.P. flanged or threaded full opening steel gate valve, or Halliburton Lo Torc Plug valve.
- 25

EXHIBIT III/IV

	TEXACO, INC WILKINS DIVISION WILKINS FIELD	
Dow "B" -33- FEDERAL		