

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-27789
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Rio Penasco RT
8. Well No. 2
9. Pool name or Wildcat Penasco Wolfcamp
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3495' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION	3. Address of Operator 105 South 4th St., Artesia, NM 88210 (505) 748-1471
4. Well Location Unit Letter K : 1980 Feet From The South Line and 1980 Feet From The West Line Section 34 Township 18S Range 25E NMPM Eddy County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3495' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Set Intermediate Casing <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 12-1/4" hole 9:30 AM 2-6-94. Ran 27 joints 8-5/8" 24# J-55 casing set 1214'. Guide shoe set 1214', float collar set 1169'. Cemented w/200 sx Class "H" + 12% Thixad + 10#/sx Gilsonite + 1/2#/sx Celloseal + 2% CaCl2 (yield 1.55, wt 14.6) and 325 sx PSL "C" + 10#/sx Gilsonite + 1/2#/sx Celloseal + 3% CaCl2 (yield 2.01, wt 12.5). Tailed in w/200 sx Class "C" Neat + 2% CaCl2 (yield 1.33, wt 14.8). PD 2:56 PM 2-6-94. Bumped plug to 750 psi, float held OK. Cement did not circulate. WOC 4 hours. Ran Temperature Survey and found TOC at 770' Ran 4 stages of 1" and cemented with 475 sx Class "C" with additives. PD 1:02 AM 2-7-94 on 4th stage. Circulated 15 sacks cement to pit on 4th stage of 1". WOC. Drilled out 2:00 PM 2-7-94. WOC 23 hours. NU and tested to 1000 psi for 15 minutes. Reduced hole to 7-7/8" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 2-9-94
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY SECRETARY, DISTRICT II TITLE SECRETARY DATE FEB 10 1994
CONDITIONS OF APPROVAL, IF ANY: