

458
dp

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-28080
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION	3. Address of Operator 105 South Fourth Street - Artesia, NM 88210	4. Well Location Unit Letter M : 330 Feet From The South Line and 990 Feet From The West Line Section 22 Township 18S Range 26E NMPM Eddy County	7. Lease Name or Unit Agreement Name Ryburn FZ	8. Well No. 2	9. Pool name or Wildcat Undesignated San Andres
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3233' GR						

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, resume drilling, surface casing and cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 4:00 PM 9-1-94. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified OCD - Artesia. Resumed drilling a 12-1/4" hole with rotary tools at 10:15 PM 9-2-94.

TD 950'. Ran 22 joints of 8-5/8" 24# J-55 (954.68') of casing set at 950'. 1-Texas Pattern notched guide shoe set at 950'. Insert float set at 906'. Cemented with 300 sacks Pace-setter Lite C, 6% gel, 10#/sack gilsonite, 1/4#/sack celloseal and 3% CaCl2 (yield 1.98, weight 12.5). Tailed in with 200 sacks "C" 2% CaCl2 (yield 1.32, weight 14.8). PD 6:15 AM 9-6-94. Bumped plug to 800#, OK. Circulated 141 sacks. WOC. Drilled out at 12:15 AM 9-7-94. WOC 18 hours. Nippled up and tested to 1000# for 10 minutes. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE 9-9-94
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505-748-1471

(This space for State Use)

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

OCT 31 1994