

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OIL CONS COMMISSION
Drawer DD
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mewbourne Oil Company

3. Address and Telephone No.

P. O. Box 5270, Hobbs, New Mexico 88241; 505 393-3905

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 560' FWL Unit "L"
Section 29 - T18S - R30E

5. Lease Designation and Serial No.

NM-27280

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Santo Nino "29" Fed. #3

9. API Well No.

30-015-28135

10. Field and Pool, or Exploratory Area

Santo Nino Bone Spring

11. County or Parish, State

Eddy, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Cement 8 5/8" Int. Csg
and Shut off water flow.
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 02-22-95: Drilled into water flow while drilling 12 1/4" intermediate hole @ depth of 630' K. B. Conferred with Shannon Shaw of Carlsbad BLM office via telephone @ 8:50 A.M. Informed him of our intentions and recieved approval to proceed with plans as outlined below. Initial water flow rate was 25 bbls./hour. Last measured rate was 18 bbls./hr.
- 02-23-95: Drilled 12 1/4" hole to 2,485' K. B. Ran 48 joints of new 8 5/8", 32#, J-55, LS 8rd, STC casing + Baker External Casing Packer + 8 more joints of 8 5/8", 32#, J-55 8rd, STC casing. Set @ 2,485' K. B. with ECP @ 351' K. B.
- 02-24-95: Halliburton cemented with 1,000 sacks of Class "C" Lite containing 1#/sack flocele + 1#/sack gilsonite + 2% CaCl₂ (wt. 13.2#/gal., yield 1.96 cu. ft./sack,) followed by 200 sacks of Class "C" Neet containing 2% CaCl₂. Circulated 240 sacks of cement to the pit. Closed annular preventor and squeezed 115 sacks of cement into water flow zone. Plug down to 2,442' @ 7:25 A.M. 02-24-95. Opened annular preventor, no water flow. Inflated ECP. Set slips and WOC 24 hours.
- 02-25-95: NU BOP stack and tested casing and stack to 1500# for 30 min. Held O.K. Drilled out shoe joint and drilled 10' of new formation. Shut down for 30 min. and checked for water flow. No flow present.

14. I hereby certify that the foregoing is true and correct

Signed

Bill Pierce

Title Drilling Superintendent


Date Feb. 28, 1995

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title



Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side