

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
Drawer DD
Artesia, NM 87003-0010
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mewbourne Oil Company

3. Address and Telephone No.

P.O. Box 5270 Hobbs, New Mexico 88241 (505) 393-5905

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 510' FWL
Sec. 29-T18S-R30E

5. Lease Designation and Serial No.

NM-27279

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Santo Nino "29" Fed. #1

9. API Well No.

10. Field and Pool, or Exploratory Area

Santo Nino Bone Spring

11. County or Parish, State

Eddy County, N.M.

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud & Cement 13-3/8"
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/16/94 MIRU WEK Drllg. Co., Rig #2. Spudded 17-1/2" surface hole @ 1:30 p.m. Drilled to 402' K.B. Ran 9 jts. of new 13-3/8", 48#, 8rd, ST&C, LS casing & set @ 402' K.B. Halliburton cemented w/200 sks. Class "C" Lite containing 1/2#/sk. flocele + 1#/sk. gilsonite + 3% CaCl2 (yield 2.02, wt. 12.4#) followed by 200 sks. Class "C" Neet containing 3% CaCl2 (yield 1.32, wt. 14.8#). Plug down @ 10:00 p.m. 11/16/94. Circ. 75 sks. to pit. Job witnessed by Jim Amos w/ Carlsbad BLM. WOC 12 hrs. NU BOP & tested to 600# for 30 minutes, ok.

600

RECEIVED
NOV 23 10 04 AM '94
CARLSBAD

ACCEPTED FOR
FILE

14. I hereby certify that the foregoing is true and correct

Signed Bill Pierce

Title Drilling Superintendent

Date 11/22/94

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date