

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-28276
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Krauss GE
8. Well No. 3
9. Pool name or Wildcat Atoka San Andres

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	
4. Well Location Unit Letter L : 1650 Feet From The South Line and 990 Feet From The West Line Section 22 Township 18S Range 26E NMPM Eddy County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3335' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, resume drilling, surface casing and cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 10:00 AM 1-23-95. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified OCD - Artesia of spud. Resumed drilling a 12-1/4" hole with rotary tools at 5:00 PM 1-25-95.

TD 1110'. Reached TD at 1:30 AM 1-28-95. Ran 25 joints of 8-5/8" 24# J-55 (1112.25') of casing set at 1110'. 1-Texas Pattern notched guide shoe set at 1110'. Insert float set at 1070'. Cemented with 350 sacks Pacesetter Lite "C" (65-35-6), 5#/sack gilsonite, 1/4#/sack celloseal and 3% CaCl<sub>2</sub> (yield 2.01, weight 12.5). Tailed in with 200 sacks Class C Neat with 2% CaCl<sub>2</sub> (yield 1.33, weight 14.8). PD 7:45 AM 1-29-95. Bumped plug to 400 psi, OK. Cement did not circulate. WOC 4 hours. Ran Temperature Survey and found top of cement at 250'. Ran 1". Tagged cement at 250'. Spotted 325 sacks Class C Neat with 2% CaCl<sub>2</sub>. PD 1:30 PM 1-29-95. Cement circulated 35 sacks to pit. WOC. Drilled out at 1:00 AM 1-30-95. WOC 17 hours and 15 minutes. Nipped up and tested to 1000# for 15 minutes. Cut off and weld on flow nipple. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. 7-7/8". Resumed drilling.

SIGNATURE Rusty Klein TITLE Production Clerk DATE 1-31-95

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUZ  
DISTRICT II SUPERVISOR

APPROVED BY

TITLE

DATE

FEB 9 1995

CONDITIONS OF APPROVAL, IF ANY: