

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATIONS COMM-
NM OIL & GAS
Drawer DD
Artesia (See other instructions on reverse side)

FORM APPROVED

dsf

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other

b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF RESRV ☐ Other

2. NAME OF OPERATOR

DEVON ENERGY CORPORATION (NEVADA)

3. ADDRESS AND TELEPHONE NO.

20 N. BROADWAY, SUITE 1500, OKC, OK 73102-8260 (405) 235-3611

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1650' FSL & 710' FEL

At top prod. interval reported below (SAME)

At total depth (SAME)

5. LEASE DESIGNATION AND SERIAL NO.
NM 7718

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
NA

7. UNIT AGREEMENT NAME
West Red Lake 8910089700

8. FARM OR LEASE NAME, WELL NO.
West Red Lake Unit #48

9. API WELL NO.
30-015-28277

10. FIELD AND POOL, OR WILDCAT
Red Lake (Q-GB-SA)

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA
Sec. 8-T18S-R27E
Unit I

14. PERMIT NO.

DATE ISSUED
12/21/94

12. COUNTY OR PARISH
Eddy

13. STATE
NM

15. DATE SPUNDED
2/16/95

16. DATE T.D. REACHED
2/21/95

17. DATE COMPL. (Ready to prod.)
4/7/95

18. ELEVATIONS OF WELL HEAD, T.O. CASINGHEAD
GL 3476'; DF 3476'; ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD
2249'

21. PLUG, BACK T.D., MD & TVD
2191'

22. IF MULTIPLE COMPL., HOW MANY*
N/A

23. INTERVALS
ROTARY TOOLS
CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*
1868' - 2128' San Andres "A", "B", "C", "D"

OIL CON. DIV.
DIST. 2

25. WAS DIRECTIONAL SURVEY
MADE
no

26. TYPE ELECTRIC AND OTHER LOGS RUN
SDL/DSN, DLL/MSFL, CBL

27. WAS WELL CORED
no

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8 5/8" J-55	24 ppf	1151'	12 1/4"	350 sx Lite & 200 sx C, TOC surf	
5 1/2" J-55	15.5 ppf	2249'	7 7/8"	100 sx Lite & 275 sx C, TOC surf	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2 7/8"	2153'	

31. PERFORATION RECORD (Interval, size and number)

1868' - 1911' (5 holes, .40" EHD) zone "A"
1918' - 1998' (10 holes, 0.40" EHD) zone "B"
2032' - 2128' (15 holes, 0.40" EHD) zones "C" & "D"

32. ACID SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
1868-1998'	2000 gals 15% NeFe acid + 30 BS
2032-2128'	2000 gals 15% NeFe acid + 30 BS
1868-2128'	36,000 gals 2% KCl + 45,000 gals X-Link gel + 174,000#
	20/40 Ottawa sd + 24,000# 20/40 RC sd

33.* PRODUCTION

DATE FIRST PRODUCTION 3/26/95		PRODUCTIONS METHOD I(Flowing, gas lift, pumping—size and type of pump) 2 1/2" x 2" x 12' pump					WELL STATUS (Producing or shut-in) P	
DATE OF TEST 4/6/95	HOURS TESTED 24	CHOKE SIZE	PROD'N FOR TEST PERIOD →	OIL-BBL. 46	GAS-MCF. 92	WATER-BBL. 63	GAS-OIL RATIO 2000.1	
FLOW. TUBING PRESS. —	CASING PRESSURE —	CALCULATED 24-HOUR RATE →	OIL-BBL. 46	GAS-MCF. 92	WATER-BBL. 63	OIL GRAVITY-API (CORR.) 39		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)
sold to GPM

TEST WITNESSED BY
D. Hokett

35. LIST OF ATTACHMENTS
logs & inclination report

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED E. L. Buttross, Jr.

E. L. BUTTROSS, JR.
TITLE DISTRICT ENGINEER

DATE July 14, 1995

*(See Instructions and Spaces for Additional Data on Reverse Side)

17. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Premier	1290'	1336'	Sandstone
San Andres	1632'	2132'	Dolomite
		DEPTH	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.. (continued from the front)

38.

GEOLOGIC MARKERS

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH
Bowers	510'	+2975
Queen	706'	+2779
Grayburg	1056'	+2429
Premier	1290'	+2195
San Andres	1336'	+2149