

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-28343
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	
Dayton EZ	
8. Well No.	3
9. Pool name or Wildcat	Atoka San Andres
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	
3558' GR	

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter H : 2310 Feet From The North Line and 990 Feet From The East Line Section 21 Township 18S Range 26E NMPM Eddy County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3558' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Production casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 1720'. Reached TD at 2:00 PM 2-27-95. Ran 43 joints of 5-1/2" 17# 8rd J-55 LT&C (1723.34') used casing set at 1720'. 1-regular guide shoe set at 1720'. Float collar set at 1715'. Cemented with 25 sacks gelled H2O ahead of 325 sacks "C" and 5/10% CF-14 (yield 1.33, weight 14.8). PD 2:45 PM 2-27-95. Bumped plug to 1100 psi for 3 minutes. Circulated 25 sacks cement. NOTE: Float and casing held okay. Released rig at 3:45 PM 2-27-95.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Rusty Klein*

TITLE

Production Clerk

DATE 3-6-95

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use) ORIGINAL SIGNED BY TIM W. GUM

APPROVED BY

TITLE

DATE

MAR 10 1995

CONDITIONS OF APPROVAL, IF ANY: