

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE

FORM APPROVED

NM 88210-2834

DESIGNATION AND SERIAL NO.
NM-LC-070937

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐
2. NAME OF OPERATOR
DEVON ENERGY CORPORATION (NEVADA)
3. ADDRESS AND TELEPHONE NO.
20 N. BROADWAY, SUITE 1500, OKC, OK 73102-8260 (405) 235-3611
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*
At surface 990' FSL & 330' FWL
At top prod. interval reported below (SAME)
At total depth (SAME)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A
7. UNIT AGREEMENT NAME
West Red Lake 8910089700
8. FARM OR LEASE NAME, WELL NO.
West Red Lake Unit #45
9. API WELL NO.
30-015-28445
10. FIELD AND POOL, OR WILDCAT
Red Lake (Q-GB-SA)
11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA
Sec. 4-T18S-R27E
Unit M

14. PERMIT NO.
DATE ISSUED 4/4/95
12. COUNTY OR PARISH
Eddy
13. STATE
NM
15. DATE SPUDDED
9/18/95
16. DATE T.D. REACHED
9/22/95
17. DATE COMPL. (Ready to prod.)
10/11/95
18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*
GL 3526'
19. ELEV. CASINGHEAD
20. TOTAL DEPTH, MD & TVD
2225'
21. PLUG, BACK T.D., MD & TVD
2146'
22. IF MULTIPLE COMPL., HOW MANY*
N/A
23. INTERVALS DRILLED BY
ROTARY TOOLS
X
CABLE TOOLS
24. PRODUCING INTERVAL(S), OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*
1723-2115' San Andres
25. WAS DIRECTIONAL SURVEY MADE
NO
26. TYPE ELECTRIC AND OTHER LOGS RUN
Dual Laterolog/MSFL, Litho-Density/Compensated Neutron and GR/CCL/Cement Bond/Variable Density logs
27. WAS WELL CORED
NO

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8 5/8" J-55	24#	1069'	12 1/4"	100 sx Lite + 350 sx Lite C +	
				200 sx Class C; TOC surface	
5 1/2" J-55	15.5#	2221'	7 7/8"	150 sx Lite + 200 sx Class C; TOC	
				at surface	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2 7/8"	2125'	

31. PERFORATION RECORD (Interval, size and number)

1723-1810' w/5 holes (.44" EHD) San Andres Alpha
1880-1915' w/3 holes (.44" EHD), San Andres "A"
1930-2020' w/8 holes (.44" EHD) San Andres "B"
2033-2062' w/7 holes (.44" EHD), San Andres "C"
2078-2115' w/6 holes (.44" EHD) San Andres "D"

32. ACID SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
1723-1810'	3000 gals 15% NeFe acid + 58 BS
	70,000 gals 30# X-Link gel + 9000# 100-Mesh sd +
	258,000# 20/40 Brady sd + 28,000# 16/30 RC sd

33.*
DATE FIRST PRODUCTION
10/13/95
PRODUCTIONS METHOD I (Flowing, gas lift, pumping—size and type of pump)
2 1/2" x 2" x 12' pump
WELL STATUS (Producing or shut-in)
Prdg
DATE OF TEST
10/20/95
HOURS TESTED
24 hrs
CHOKE SIZE
PROD'N FOR TEST PERIOD
OIL-BBL.
95
GAS-MCF.
190
WATER-BBL.
91
GAS-OIL RATIO
2000/1
FLOW. TUBING PRESS.
CASING PRESSURE
CALCULATED 24-HOUR RATE
OIL-BBL.
95
GAS-MCF.
190
WATER-BBL.
91
OIL GRAVITY-API (CORR.)
39°

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)
sold to GPM Gas Svcs
TEST WITNESSED BY
Danny Hokett
ACCEPTED FOR RECORD

35. LIST OF ATTACHMENTS
open hole logs, deviation survey report and bond log

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED E. L. Buttross Jr.E. L. BUTTROSS, JR.
TITLE DISTRICT ENGINEER

DATE November 27, 1995

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries);				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Premier Sand San Andres	1326' 1360'	1343 2226'	sandstone dolomite	Bowers Queen Grayburg Premier San Andres	534' 719' 1084' 1326' 1360'	+3000' +2715' +2450' +2208' +2174'
		DEPTH	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.. (continued from the front)			
			N/A			