

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE**Southeastern New Mexico**

T. Anhy _____
 T. Salt _____
 B. Salt _____
 T. Yates _____
 T. 7 Rivers _____
 T. Queen _____ 432'
 T. Grayburg _____ 789'
 T. San Andres _____ 1046'
 T. Glorieta _____
 T. Paddock _____
 T. Blinbry _____
 T. Tubb _____
 T. Drinkard _____
 T. Abol _____
 T. Wolfcamp _____
 T. Penn _____
 T. Cisco (Bough C) _____

T. Canyon**T. Strawn****T. Atoka****T. Miss****T. Devonian****T. Silurian****T. Montoya****T. Simpson****T. McKee****T. Ellenburger****T. Gr. Wash****T. Delaware Sand****T. Bone Springs****T. _____****T. _____****T. _____****T. _____****Northwestern New Mexico**

T. Ojo Alamo _____
 T. Kirtland-Fruitland _____
 T. Pictured Cliffs _____
 T. Cliff House _____
 T. Menefee _____
 T. Point Lookout _____
 T. Mancos _____
 T. Gallup _____
 Base Greenhorn _____
 T. Dakota _____
 T. Morrison _____
 T. Todilto _____
 T. Entrada _____
 T. Wingate _____
 T. Chinle _____
 T. Permian _____
 T. Penn "A" _____

T. Penn. "B"**T. Penn. "C"****T. Penn. "D"****T. Leadville****T. Madison****T. Elbert****T. McCracken****T. Ignacio Otzte****T. Granite****T. _____****T. _____****T. _____****T. _____****T. _____****T. _____****T. _____****T. _____****OIL OR GAS SANDS OR ZONES**

No. 1, from 1016' to 1046' No. 3, from _____ to _____
 No. 2, from 1357' to 1891' No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
 No. 2, from _____ to _____ feet
 No. 3, from _____ to _____ feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	1357'	1357'	Anhydrite/Dolomite				
1357'	2000'	643'	Dolomite				
			(Continued from the front)				
			ACID SHOT, FRACTURE				
			1,000 gals PrePad + 2 drum				
			Pro-Kem scale inhibitor +				
			180,000 gals 30# gel water				
			+ 6,000# 100 mesh sand +				
			243,000# 20/40 brady sand				