

CISF
11

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd, Aztec, NM
87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-28455
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name West Red Lake Unit
8. Well No. 55
9. Pool name or Wildcat Red Lake (Q-GB-SA)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT
(FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED
FEB 11 1997
OIL CON. DIV.
DIST. 2
(405) 235-3611

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other _____
2. Name of Operator DEVON ENERGY CORPORATION (NEVADA)
3. Address of Operator 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102

4. Well Location Unit Letter <u>K-1650</u> Feet From The <u>SOUTH</u> Line and <u>1650'</u> Feet From The <u>WEST</u> Line
Section <u>7</u> Township <u>18S</u> Range <u>27E</u> NMPM Eddy County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) <u>GL 3283'</u>

Check Appropriate Box To Indicate Nature Of Notice, Report, Or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: _____ ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud casing strings TD ☒

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103.

Spudded this well on 12/19/96 at 2200 hrs and drld a 17-1/2" hole to 200'. On 12/20/96 ran 6 jts 13-3/8" 48# H-40 ST&C csg, set @ 233'. Cmt'd w/275 sxs cl "C" cmt. TOC @ surface. *WOC ? hr*

Drld 12-1/4" hole to 926'. On 12/22/96 ran 22 jts of 8-5/8" 24# J-55 ST&C csg, set @ 925'. Cmt'd w/300 sxs lite "C" and 250 sxs cl "C". TOC surface. *WOC ? hr*

Drld 7-7/8" hole and reached TD of 2000' on 12/27/96 at 1900 hrs. Schlumberger ran DLL/MSFL and LDT/CNL/GR logs. Ran 48 jts of 5-1/2", 15.5# J-55 LT&C csg, set @ 1999'. Cmt'd w/345 sxs cl "H" cmt. TOC surface.

Released rig @ 0130 hrs on 12/29/96. WOCU.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *Diana M. Keys*
TYPE OR PRINT NAME Diana Keys

TITLE ENGINEERING TECHNICIAN

DATE February 7, 1997

TELEPHONE NO. (405) 235-3611

(This space for State use)

Approved by *ORIGINAL SIGNED BY TIM W. GUM*
Conditions of approval, if any: _____

TITLE _____

DATE FEB 21 1997