

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>Gates Petr. Corp.</u>		Lease <u>Krauss "GF"</u>		Well # <u>3</u>	
Location of Well	Unit <u>K</u>	Section <u>22</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor <u>NA.</u>			Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>12 1/4</u>	<u>* 8 5/8</u>	<u>24#</u>		<u>1100'</u>	<u>250 Circ</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>15.5</u>		<u>TD</u>	<u>100</u>

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____

(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required _____Type of Shoe used guide Float collar used insert Btm 3 jts welded yesTD of hole 1095' Set 1095' Feet of 8 5/8" Inch 24 # Grade 3.55New used csg. @ 1095' with 200 2% sacks neat cement around shoe+ 350 sax Pacesetter etc. additives 1/4 # celo., 5 # gils., 39ccsPlug down @ 1345 (AM) (PM) Date 6-9-95Cement circulated No No. of Sacks 0Cemented by Western Company Witnessed by Mike StubblefieldTemp. Survey ran @ 5:45 (AM) (PM) Date 6-9-95 top cement @ 136' *

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks:

* Ran 1" tubing and tagged to c 160'

Pumped 250 sx cl c. 39ccs.

12 1/4" hole R.T. - 38 hours.

Cement circ. to surface.

L.D.B. - 950'