

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-28460
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Krauss GF
8. Well No.	3
9. Pool name or Wildcat	Atoka San Andres
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	3327' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. Name of Operator
YATES PETROLEUM CORPORATION
3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter K : 1650 Feet From The South Line
Section 22 Township 18S Range 2E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3327' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Spud, resume drilling, surface casing & cement <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
Spudded a 26" hole with rat hole machine at 10:30 AM 6-10-95. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified OCD - Artesia of spud. Resumed drilling a 12-1/4" hole with rotary tools at 1:15 PM 6-11-95.

TD 1095'. Ran and landed 24 joints of 8-5/8" 24# 8rd J-55 ST&C (1076.58') of casing set at 1091' with 14' landing joint. 1-Texas Pattern notched guide shoe set at 1091'. Float collar set at 1046'. Cemented with 350 sacks Pacesetter Lite C, 1/4#/sack celloseal, 5#/sack gilsonite and 3% CaCl2 (yield 1.84, weight 12.7). Tailed in with 200 sacks "C" with 2% CaCl2 (yield 1.32, weight 14.8). PD 1:45 PM 6-13-95. Bumped plug to 900 psi, OK. Cement did not circulate. WOC 5 hours. Ran Temperature Survey and found top of cement at 160'. Ran 1". Tagged at 136'. Spotted 250 sacks "C" with 3% CaCl2. PD 7:45 PM 6-13-95. Circulated 15 sacks to pit. WOC. Drilled out at 7:45 AM 6-14-95. WOC 17 hours. Nippled up and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE Rusty Klein TITLE Production Clerk DATE June 16, 1995
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)
APPROVED BY ORIGINAL SIGNED BY TIM W. GUM TITLE DISTRICT II SUPERVISOR DATE JUN 23 1995
CONDITIONS OF APPROVAL, IF ANY: