

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
Drawer DD
Artesia, NM 88210
FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other	8. Well Name and No. Scout EH Federal Com #6
2. Name of Operator YATES PETROLEUM CORPORATION (505) 748-1471	9. API Well No. 30-015-28499
3. Address and Telephone No. 105 South 4th St., Artesia, NM 88210	10. Field and Pool, or Exploratory Area Penasco Draw Wolfcamp
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1980' FNL & 1980' FEL of Section 34-T18S-R25E (Unit G, SWNE)	11. County or Parish, State Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input checked="" type="checkbox"/> Other Spud, surface casing & cement
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 26" hole with rat hole machine at 10:45 AM 5-19-95. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified BLM - Carlsbad Answering Service of spud. Resumed drilling a 17-1/2" hole with rotary tools at 3:30 PM 5-22-95.

TD 420'. Reached TD at 9:45 PM 5-22-95. Ran 9 joints of 13-3/8" 48# J-55 (421.50') of casing set at 417'. 1-Texas Pattern notched guide shoe set at 417'. Insert float set at 376'. Cemented with 250 sacks Pacesetter Lite C, 10#/sack gilsonite, 1/4#/sack cello-seal and 3% CaCl2 (yield 2.01, weight 14.48). Tailed in with 200 sacks Class C Neat 2% CaCl2 (yield 1.32, weight 14.8). PD 2:30 AM 5-23-95. Bumped plug to 400 psi, OK. Circulated 50 sacks to pit. WOC. Drilled out at 9:30 PM 5-23-95. WOC 19 hours. Cut off and weld on flow nipple. Reduced hole to 12-1/4". Resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed Rusty K. Green Title Production Clerk Date May 31, 1995

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any: