

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE 3*

FORM APPROVED

451

(See other instructions on reverse side)

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF RESVR ☐ Other ☐
2. NAME OF OPERATOR
DEVON ENERGY CORPORATION (NEVADA)
3. ADDRESS AND TELEPHONE NO.
20 N. BROADWAY, SUITE 1500, OKC, OK 73102-8260 (405) 235-3611
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*
At surface 680' FSL & 1650' FWL
At top prod. interval reported below (SAME)
At total depth (SAME)

5. LEASE DESIGNATION AND SERIAL NO.
NM-NM-7720
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
NA
7. UNIT AGREEMENT NAME
West Red Lake 8910089700
8. FARM OR LEASE NAME, WELL NO.
West Red Lake Unit #43
9. API WELL NO.
30-015-28564
10. FIELD AND POOL, OR WILDCAT
Red Lake (Q-GB-SA)
11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA
Sec. 4-T18S-R27E
Lot 18

14. PERMIT NO.
DATE ISSUED 6/19/95
12. COUNTY OR PARISH
Eddy
13. STATE
NM
15. DATE SPUDDED 9/12/95
16. DATE T.D. REACHED 9/17/95
17. DATE COMPL. (Ready to prod.) 10/1/95
18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*
GL 3587'
19. ELEV. CASINGHEAD
20. TOTAL DEPTH, MD & TVD 2330'
21. PLUG, BACK T.D., MD & TVD 2256'
22. IF MULTIPLE COMPLETIONS, LIST INTERVALS, MD & TVD, AND CEMENT TYPE
N/A
23. IF MULTIPLE COMPLETIONS, LIST INTERVALS, MD & TVD, AND CEMENT TYPE
N/A
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*
1815-2190' San Andres
25. WAS DIRECTIONAL SURVEY MADE
no
26. TYPE ELECTRIC AND OTHER LOGS RUN
dual Laterolog/MSFL, Litho-Density/Compensated Neutron and Cement Bond logs
27. WAS WELL CORED
no

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8 5/8" J-55	24#	1199'	12 1/4"	400 sx Lite & 200 sx C, TOC surf	
5 1/2" J-55	15.5#	2299'	7 7/8"	150 sx Lite & 250 sx C, TOC surf	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2 7/8"	2198'	

31. PERFORATION RECORD (Interval, size and number)

1805-1829' w/3 holes (.40" EHD) San Andres Alpha
1970-2006' w/4 holes (.40" EHD), San Andres "A"
2025-2106' w/8 holes (.40" EHD) San Andres "B"
2127-2167' w/8 holes (.40" EHD), San Andres "C"
2186-2190' w/3 holes (.40" EHD) San Andres "D"

32. ACID SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
1805-2190'	2500 gals 15% NeFe acid + 52 BS
	1000 gals Un-X-Link gel prepad + 50,000 gals 30#
	X-Link gel + 5000# 100-Mesh sd + 174,000#
	20/40 Brady sd + 21,000# 16/30 RC sd

33. PRODUCTION

DATE FIRST PRODUCTION 10/4/95
PRODUCTIONS METHOD I (Flowing, gas lift, pumping—size and type of pump) 2 1/2" x 2" x 12' pump
WELL STATUS (Producing or shut-in) Prdg

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL-BBL.	GAS-MCF.	WATER-BBL.	GAS-OIL RATIO
10/11/95	24 hrs			69	138	125	2000/1

FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL.	GAS-MCF.	WATER-BBL.	OIL GRAVITY-API (CORR.)
--	--		69	138	125	39°

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)
sold to GPM Gas Svcs

TEST WITNESSED BY
Danny Hokett

35. LIST OF ATTACHMENTS
electric logs, deviation survey and bond log

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED E. L. BUTTROSS, JR.

TITLE DISTRICT ENGINEER

DATE November 14, 1995

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Premier Sand San Andres	1410'	1428	sandstone	Bowers	614'	+2981'
	1736'	2225'		Queen	802'	+2793'
			Grayburg	1174'	+2421'	
			Premier	1410'	+2185'	
			San Andres	1448'	+2147'	
		DEPTH	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.. (continued from the front)			
			N/A			