

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

CONTACT RECEIVING  
OFFICE FOR NUMBER  
OF COPIES REQUIRED  
(Other instructions on re-  
verse side)

BHM Roswell District  
Modified Form No.  
NM060-3160-4

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		3a. Area Code & Phone No. 505-676-2266		5. LEASE DESIGNATION AND SERIAL NO. LC-029415 B	
2. NAME OF OPERATOR W.A. & E.R. HUDSON, INC.				6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P.O. Box 9, Maljamar, NM 88264-0009				7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 2630' FEL and 20' FNL of Section 25				8. FARM OR LEASE NAME PUCKETT B	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, OR, etc.)		9. WELL NO. 34	
				10. FIELD AND POOL, OR WILDCAT Malj. G-SA	
				11. SEC., T., R., M., OR BLK. AND SURVEY OR ADMA Sec. 25, T17S, R31E	
				12. COUNTY OR PARISH Eddy	
				13. STATE NM	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
(Other) ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
ABANDON\* ☐  
CHANGE PLANS ☐

WATER SHUT-OFF ☐  
FRACTURE TREATMENT ☐  
SHOOTING OR ACIDIZING ☐  
(Other) Cement Casing ☐  
REPAIRING WELL ☐  
ALTERING CASING ☐  
ABANDONMENT\* ☒

17. DESCRIBE PROMISED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

On October 2, 1995, cemented 13-3/8" OD 44# J-55 casing at 615' with 700 sx. premium plus with 2% CaCl. Cement circulated to surface.

On October 4, 1995, cemented 8-5/8" OD 24# J-55 casing at 1928' with 700 sx. premium plus with 2% CaCl. Cement circulated to surface.

On October 10, 1995, cemented 5-1/2" OD 15.5# J-55 casing at 4018' with 250 sx. premium plus with 6# salt.

RECEIVED

APR 01 1996

OIL CON. DIV.

ACCEPTED FOR RECORD

MAR 20 1996

CARLSBAD, NM 88502

18. I hereby certify that the foregoing is true and correct

SIGNED J.B. Smith TITLE Prod. Supt. DATE 11/2/95

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

NOV 14 1966

LIBRARY OF THE

U.S. AIR FORCE