			CIST
rm 3160-5 ne 1990)	UNITED STA DEPARTMENT OF TH BUREAU OF LAND MA	E INTERIOR	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No.
	SUNDRY NOTICES AND RE orm for proposals to drill or to d Jse "APPLICATION FOR PERMIT	eepen or reentry to a different reservoir.	6. If Indian, Allottee or Tribe Name
	SUBMIT IN TRIP	7. If Unit or CA, Agreement Designation	
Type of Well Oil & Gas Well & Well	Other		8. Well Name and No.
	LEUM CORPORATION	(505) 748–1471)	Sand Tank APS Fed Com #1 9. Api Well No.
	th St., Artesia, NM 8821	0	30-015-28692 10. Field and Pool, or Exploratory Area
	nge, Sec., T., R., M., or Survey Description) 2145' FWL of Section 12-7	18S-R29E (Unit N, SESW)	Wildcat Sand Tank Morrow/St 11. County or Parish, State
CHECK	APPROPRIATE BOX(s) TO IN	DICATE NATURE OF NOTICE, REPO	Eddy Co., NM DRT, OR OTHER DATA
TYPE OF	SUBMISSION	TYPE OF ACTIO	N ROME T
Notice	of Intent	Abandonment Recompletion	Change 67 Plans C C Change 67 Plans C C C C C C C C C C C C C C C C C C C
X Subseq	uent Report	Plugging Back Casing Repair	Non-Routine Fracturing 2
Final A	Abandonment Notice	Altering Casing X Other Production casing &	Dispose Water
	ompleted Operations (Clearly state all pertinent det cations and measured and true vertical depths for	cement ails, and give pertinent dates, including estimated date of start	(Note: Report results of multiple considerin on Well Completion or Recompletion Réport and Log form)
(4847.07'); S-95 8rd LT& Float collar H20 spacer, 1300 sacks H weight 12.4) 322 and 4% (1/2 bbl over	f 5-1/2" 17# S-95 8rd LT& 124 joints of 5-1/2" 17# &C (575.47') (Total 11711 r set at 11653'. Preflus 12 bbls mudflush, 10 bbl Howco Lite "H", 5#/sack s). Tailed in with 625 sa CFR3 (yield 1.67, weight	A-17-96. Ran 283 joints of 5- ac (1145.39'); 117 joints of 5 A N-80 8rd LT&C (5143.08') and L.01') of casing set at 11699' shed with 150 bbls nitrified w Ls H20, 12 bbls superflush and salt, 3% Halad 322 and 5#/sack acks Super H, 5#/sack gilsonit 13.0). PD 9:45 AM 1-20-96. and shut down. Final differ ig at 12:45 PM 1-20-96.	-1/2" 17# L-80 8rd LT&C 14 joints of 5-1/2" 17# . Float shoe set at 11699'. ith 150 scf/bb1, 20 bb1s 10 bb1s H20. Cemented with gilsonite (yield 2.06, e, 1#/sack salt, 5% Halad Did not bump plug. Pumped
Waiting on o	completion unit.		
			505
\cap			
I hereby certify that the Signed TUS	he foregoing is the and correct	TiteProduction Clerk	Date Jan. 26, 1996
(This space for Federa Approved by		Title	Date
Conditions of approva			
	001, makes it a crime for any person knowingly a by matter within its jurisdiction.	nd willfully to make to any department or agency of the Um	ted States any false, fictutious or fraudulent statements
	*S	ee Instruction on Reverse Side	