

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mewbourne Oil Company

3. Address and Telephone No.

P.O. Box 5270 Hobbs, New Mexico 88241

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 1980' FEL Unit Letter "G"
Sec 29-T18S-R30E

5. Lease Designation and Serial No.

NM-27279

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Santo Nino "29" Federal

9. API Well No.

30-015-28698

10. Field and Pool, or Exploratory Area

Santo Nino Bone Spring

11. County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spudding, Cmt. Surface
csg. & Inter.

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRU WEK Drilling Company, Rig #2. Spudded 17-1/2" surface hole at 11:45 a.m. 02/20/96. BLM was notified, no representative present. Ran 10 joints of 13-3/8", 48#, J-55, ST&C new casing and set at 400'. Halliburton cemented with 200 sacks of Class "C" Lite containing 3% CaCl₂ + 0.5#/sack flocele + 1#/sack gilsonite, followed by 200 sacks of Class "C" Neet containing 3% CaCl₂. Plug down at 8:30 p.m. 02/20/96. BLM was notified, no representative present. Circulated 156 sacks to pit. NU BOP and tested BOP and casing to 600# for 30 min.

Drilled 12-1/4" Intermediate hole to a depth of 1950' KB. Ran 47 joints of 8-5/8", 24#, J-55, new ST&C casing and set at 1954' KB. Halliburton cemented with 700 sacks of Class "C" Lite containing 2% CaCl₂ + 12#/sack salt + 1#/sack gilsonite + 1/2#/sack flocele followed by 200 sacks of Class "C" Neet containing 2% CaCl₂. Plug down at 4:15 a.m. on 02/23/96. Circulated 133 sacks cement to pit. BLM was notified, no representative present.

14. I hereby certify that the foregoing is true and correct

Signed

Robert C. Jones

Title Engineer

Date March 20, 1996

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side