

Form 1060-ED
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1064-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mewbourne Oil Company

3. Address and Telephone No.

P.O. Box 5270 Hobbs, New Mexico 88241

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 1980' FEL Unit Letter "G"
Sec 29-T18S-R30E

5. Lease Designation and Serial No.

NM-27279

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Santo Nino "29" Federal

9. API Well No.

30-015-28698

10. Field and Pool, or Exploratory Area

Santo Nino Bone Spring

11. County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Drilled 7-7/8" production hole to a depth of 8450'. Ran E-logs and elected to plug and abandon well. Notified BLM of election to plug and abandon well with plugging procedures on 03/12/96. Set 35 sacks of Class "C" Neet plug from 7200' - 7300'. Set 35 sacks of Class "C" Neet plug from 4280' - 4380'. Set 45 sacks Class "C" Neet with 3% CaCl2 from 1900' - 2000'. WOC for 4 hours and tagged with slickline at 1835'. Set 30 sacks Class "C" Neet plug from 350' - 450'. Set 30 sacks Class "C" Neet surface plug at 50', circulated 10 sacks to surface. Cut off wellhead, installed dry hole marker. Rig released at 7:00 a.m. 03/12/96. BLM was notified of plugging, no representative present.

Approved as to plugging of the well bore
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

Robert G. Jones

Title Engineer

Date March 20, 1996

(This space for Federal or State office use)

Orig. Signed by Shannon J. Shaw

PETROLEUM ENGINEER

Approved by

Conditions of approval, if any:

Title

Date

4/15/96

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side