Form 3160-5 (June 1990)

any matter within its jurisdiction.

UT ED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

C CONSERVATION DIV 811 S. 1st ST. ARTESIA, NM 882 FORM APPROVED ARTESIA, NM 882 FORM APPROVED

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals SUBMIT IN TRIPLICATE MAY 2.9 1303	NM-7721 6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE Type of Well WAY 2 9 1303	
SUBMIT IN TRIPLICATE Type of Well MAY 2 9 1303	6 If Indian Allottee or Tribe Name
Type of Well	
MAY 2 9 1995	N/A
	7. If Unit or CA, Agreement Designation
	Mark Dad Lake Linit 9010090700
M V" U 18/21 U Other	West Red Lake Unit 8910089700 8. Well Name and No.
Name of Operator	o. Well Name and No.
DEVOIT ENERGY CONTROL (1222)	West Red Lake Unit #61
3. Address and Telephone No.	9. API Well No.
	30-015-28709
	10. Field and Pool, or Exploratory Area
Location of Well (Footage, Sec., T., R., M., or Survey Description)	Red Lake (Q-GB-SA)
	11. County or Parish, State
	Eddy County, NM
THE OF NOTICE DEPOR	T OR OTHER DATA
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	I, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION	
Notice of Intent Abandonment	Change of Plans
Notice of Intent Recompletion	New Construction
Subsequent Report Plugging Back	Non-Routine Fracturing
Casing Repair	Water Shut-Off
Final Abandonment Notice Altering Casing	Conversion to Injection
Other Spud, TD'd & set csg	Dispose Water ote: Report results of multiple completion on Well
	empletion or Recompletion Report and Log form.)
Spud well @ 15:00 hrs, 3/22/96. Ran 8 5/8" surface csg as follows: 24 jts, 8 5/8", 24#, J-55, 8rd ST&C, float collar @ 970'. Cemented csg as follows: Lead - 300 sx 35/65 POZMIX "C"+ 6% gel - Tail - 200 sx Class "C" + 2% CaCl ₂ + 1/4 pps flocele. Circ'd cm Reached TD of 2400' @ 22:15 hrs, 3/26/96. Ran 5 1/2" prod csg as follows: 56 jts, 5 1/2", 15.50#, J-55, 8rd, 2420'	+ 2% CaCl ₂ + 1/4 pps flocele. It to surface. 2. Float shoe @ 2400', float
collar @ 2361'. Cemented csg as follows: Lead - 125 sx POZMIX "C" + 5 pps salt + 1/2 yield 1.94 cft/sk). Tail - 325 sx Class "C" + 2% KCl + .3% FL-5: ppg, yield 1.34 cft/sk). Circ'd cmt to surface.	/4 pps celloflakes, (wt 12.7 ppg, 2 + 1/4 pps celloflakes, (wt 14.
collar @ 2361'. Cemented csg as follows: Lead - 125 sx POZMIX "C" + 5 pps salt + 1/2 yield 1.94 cft/sk). Tail - 325 sx Class "C" + 2% KCl + .3% FL-5/2 ppg, yield 1.34 cft/sk). Circ'd cmt to surface.	/4 pps celloflakes, (wt 12.7 ppg, 2 + 1/4 pps celloflakes, (wt 14.
collar @ 2361'. Cemented csg as follows: Lead - 125 sx POZMIX "C" + 5 pps salt + 1/2 yield 1.94 cft/sk). Tail - 325 sx Class "C" + 2% KCl + .3% FL-5/2 ppg, yield 1.34 cft/sk). Circ'd cmt to surface.	/4 pps celloflakes, (wt 12.7 ppg. 2 + 1/4 pps celloflakes, (wt 14.
collar @ 2361'. Cemented csg as follows: Lead - 125 sx POZMIX "C" + 5 pps salt + 1/2 yield 1.94 cft/sk). Tail - 325 sx Class "C" + 2% KCl + .3% FL-5: ppg, yield 1.34 cft/sk). Circ'd cmt to surface. 14. I hereby certify that the foregoing is true and correct ERNIE BUTTROSS Tail DISTRICT ENGINEER	/4 pps celloflakes, (wt 12.7 ppg, 2 + 1/4 pps celloflakes, (wt 14. Date 04/30/96
collar @ 2361'. Cemented csg as follows: Lead - 125 sx POZMIX "C" + 5 pps salt + 1/2 yield 1.94 cft/sk). Tail - 325 sx Class "C" + 2% KCl + .3% FL-5: ppg, yield 1.34 cft/sk). Circ'd cmt to surface. 14. I hereby certify that the foregoing is true and correct ERNIE BUTTROSS Title DISTRICT ENGINEER	2 + 1/4 pps celloflakes, (wt 14.
collar @ 2361'. Cemented csg as follows: Lead - 125 sx POZMIX "C" + 5 pps salt + 1/2 yield 1.94 cft/sk). Tail - 325 sx Class "C" + 2% KCl + .3% FL-5: ppg, yield 1.34 cft/sk). Circ'd cmt to surface. 14. Thereby certify that the foregoing is true and correct Signed ERNIE BUTTROSS Title DISTRICT ENGINEER (This space for Federal or State office use)	2 + 1/4 pps celloflakes, (wt 14.
collar @ 2361'. Cemented csg as follows: Lead - 125 sx POZMIX "C" + 5 pps salt + 1/2 yield 1.94 cft/sk). Tail - 325 sx Class "C" + 2% KCl + .3% FL-5/2 ppg, yield 1.34 cft/sk). Circ'd cmt to surface. 14. I hereby certify that the foregoing is true and correct Signed E. J. B. Title DISTRICT ENGINEER (This space for Federal or State office use) Approved by Title	2 + 1/4 pps celloflakes, (wt 14.
collar @ 2361'. Cemented csg as follows: Lead - 125 sx POZMIX "C" + 5 pps salt + 1/2 yield 1.94 cft/sk). Tail - 325 sx Class "C" + 2% KCl + .3% FL-5/2 ppg, yield 1.34 cft/sk). Circ'd cmt to surface. 14. Thereby certify that the foregoing is true and correct ERNIE BUTTROSS Title DISTRICT ENGINEER (This space for Federal or State office use)	2 + 1/4 pps celloflakes, (wt 14.
collar @ 2361'. Cemented csg as follows: Lead - 125 sx POZMIX "C" + 5 pps salt + 1/2 yield 1.94 cft/sk). Tail - 325 sx Class "C" + 2% KCl + .3% FL-5/2 ppg, yield 1.34 cft/sk). Circ'd cmt to surface. 14. I hereby certify that the foregoing is true and correct Signed E. J. B. Title DISTRICT ENGINEER (This space for Federal or State office use) Approved by Title	2 + 1/4 pps celloflakes, (wt 14.