Submit 3 Copies to Appropriate District Office	State of New Mexico Liergy, Minerals and Natural Resources Department					Form C-103 Revised 1-1-89	CISÍ	
<u>DISTRICT I</u> P.O. Box 1980, Hobbs, NM 88240		WELL API NO. 03-015-28838		— <i>Y</i>				
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	P.O. Box 2088 Santa Fe, New Mexico 87504-2088				5. Indicate Type	of Lease	EEE M	
DISTRICT III 1000 no Brazos Rd, Aztec, NM 87410		6. State Oil & C		FEE 🛛				
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (FORM C-101) FOR SUCH PROPOSALS.)						7. Lease Name or Unit Agreement Name West Red Lake Unit		
1. Type of Well  Oil Well  Gas Well	Other	OTT ON SOCITE NOT	OOAL	- Company of the County of the				
2. Name of Operator DEVON ENERGY C	ORPORATION (N	NEVADA)		RECEIVE	Well No. 68			
3. Address of Operator				AUG 0 0 1006	9. Pool name or			
20 NORTH BROAD	WAY, SUITE 1500	), OKLAHOMA CITY,	OKLAH	OMA 73102 (494) 135-260 1995	Red Lake	(Q-GB-SA)		
4 Well Location Unit Letter F: 231	10 Feet From The	north		Office and 1700 Feet F	√/ rom-The <u>west</u>	Line		
Section 7	Township 18S	<b>3</b>	Range	27E (7) (7) NMPM	Eddy	County		
	10. Elevation (Show whether DF, RKB, RT, GR, etc.)							
		GL 3287'						
	Check Approp	priate Box To Indi	cate N	lature Of Notice, Report, Or Oth	er Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:								
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING		LUG AND ABANDON HANGE PLANS		REMEDIAL WORK  COMMENCE DRILLING OPNS.  CASING TEST AND CEMENT JOB		IG CASING ND ABANDONM	_	
OTHER:				OTHER: <u>Spud, casing strings, TD</u> nent dates, including estimated date of starting any			⊠	
We spud this well on 04-17-96 at 1700 hrs and drld a 17 1/2" hole to 180'. On 04-18-96 ran 3 jts 13 3/8" 48# H-40 ST&C csg, set at 180'. Cemented w/275 sx Class C. TOC at surface. Topped out 13 3/8" conductor w/3 yds Redi-mix.  Drld 12 1/4" hole to 900'. On 04-20-96 ran 21 jts 8 5/8" 24# J-55 ST&C csg, set at 900'. Cemented w/200 sx Class C + 400 sx 35/65 Pozmix "C" + topped out w/2 yds of Redi-Mix. TOC at surface.  Drld 7 7/8" hole and reached TD 2000' on 04-23-96 at 0230 hrs. Schumberger ran DLL/MSFL and LDT/CNL/GR logs. Ran 47 jts 5 1/2" 15.5# J-55 LT&C csg, set at 2000'. Cemented w/125 sx 35/65 Pozmix "C" + 200 sx Class "C". TOC at surface.  Released rig at 0500 hrs 04-24-96. WOCU.								
I hereby certify that the information	n above is true and c	complete to the best of my	knowle	dge and belief.				
SIGNATURE	Li Tra	ham	TITLE	ENGINEERING TECHNICIAN	DATE Aug	ust 24, 1996		
TYPE OR PRINT NAME C	Candi Graham				TELEPHON	E NO. (405) 235	-3611	
(This space for State use ORIGINA Approved by DISTRIC Conditions of approval, if any:	AL SIGNED B IT II SUPERVI	Y TIM W. GUM ISOR	TITLE		DATE	SEP 6 19	996	