State of New Mexico Form C-103 Submit 3 Copies Revised 1-1-89 to Appropriate Liergy, Minerals and Natural Resources Department District Office DISTRICT I WELL API NO. P.O. Box 1980, Hobbs, NM 88240 OIL CONSERVATION DIVISION 03-015-28875 DISTRICT II P.O. Box 2088 5. Indicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 STATE FEE 🔯 Santa Fe, New Mexico 87504-2088 DISTRICT III 6. State Oil & Gas Lease No. 1000 rio Brazos Rd, Aztec, NM 87410 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS West Red Lake Unit (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well Gas Well Oil Well Other 8. Well No. 2. Name of Operator **DEVON ENERGY CORPORATION (NEVADA)** -67 9 Pool name or Wildcat 3. Address of Operator 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 4005 235 Red Lake (Q-GB-SA) 4 Well Location Unit Letter __ C : 330 Feet From The __north Line and 1400 Feet From The west NMPM Township 18S 27E Range Eddy County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) GL 3299' Check Appropriate Box To Indicate Nature Of Notice, Report, Or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON **REMEDIAL WORK ALTERING CASING CHANGE PLANS TEMPORARILY ABANDON** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHER: _Spud, casing strings, TD OTHER: 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. We spud this well on 04-25-96 at 0530 hrs and drld a 17 1/2" hole to 175'. Then ran 4 jts 13 3/8" 48# H-40 ST&C csg, set at 141'. Cemented w/375 sx Class C. Topped w/450 sx Class "C". TOC at 59' from surface. Topped out 13 3/8" conductor w/10 yds Redi-mix. LOC ? Drld 12 1/4" hole to 903'. On 04-28-96 ran 21 its 8 5/8" 24# J-55 ST&C csg, set at 903'. Cemented w/300 sx Class C + 300 sx 35/65 Pozmix "C" + topped out w/7 yds of Redi-Mix. TOC at surface. 400 C - 7 Drld 7 7/8" hole and reached TD 2000' on 05-02-96 at 0530 hrs. Schumberger ran DLL/MSFL and LDT/CNL/GR logs. Ran 48 jts 5 1/2" 15.5# J-55 LT&C csg, set at 2000'. Cemented w/125 sx 35/65 Pozmix "C" + 250 sx Class "C". TOC at surface. Released rig at 0045 hrs 05-03-96. WOCU. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE ENGINEERING TECHNICIAN DATE August 24, 1996 TYPE OR PRINT NAME Candi Graham TELEPHONE NO. (405) 235-3611 (This space for State use) ORIGINAL SIGNED BY TIM W. GUM DISTRICT II SUPERVISOR 6 1996 Approved by TITLE

Conditions of approval, if any: