

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-015-28876

Operator <u>Gates Petr. Corp</u>		Lease <u>Lawrence ADZ</u>		Well # <u>2</u>	
Location of Well	Unit <u>H</u>	Section <u>32</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor	<u>L + M</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

* Witness 8 5/8

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>12 1/4</u>	* <u>8 5/8</u>	<u>24 #</u>		<u>1100'</u>	<u>900 Circ</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>15.5 #</u>		<u>TD</u>	<u>300</u>

Casing Data:

Surface _____ joints of 8 5/8" inch 24 # Grade 5-55

(Approved) (Rejected) _____

Inspected by m s. date 3-26-96

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required _____

Type of Shoe used guide Float coliar used insert Btm 3 jts welded yes

TD of hole 1060' Set 1060' Feet of 8 5/8" Inch 24 # Grade 5-55

New used csg. @ 1060' with 200 270cc sacks neat cement around shoe

+ 325 sax 65/35 803-C additives 5# gilsonite, 1/4" celoseal, 270cc

Plug down @ 4:15 (AM) (PM) Date 3-27-96

Cement circulated yes No. of Sacks 1215x

Cemented by B. J. Hughes Witnessed by Mike Stubblefield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

12 1/4" hole R.T. 32 Hrs L.D.B. - 955'