

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Encl Minerals and Natural Resources Department

Form C-183  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-28877
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Ryburn FZ
8. Well No. 3
9. Pool name or Wildcat Atoka San Andres
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3340' GR

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210
4. Well Location Unit Letter M : 990 Feet From The South Line and 990 Feet From The West Line Section 22 Township 18S Range 26E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
	OTHER: Resume drilling, surface casing & cmt <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Resumed drilling a 12-1/4" hole with rotary tools at 2:00 PM 4-16-96. OIL CON. DIV. DIST. 2

TD 1116'. Reached TD at 5:30 PM 4-13-96. Ran 13 joints of 8-5/8" 24# J-55 8rd ST&C (573.56') of casing set at 570'. 1-Texas Pattern notched guide shoe set at 570'. Insert float set at 526'. Cemented with 100 sacks Thixad, 5#/sack gilsonite and 1/4#/sack celloseal (yield 1.51, weight 14.7) and 325 sacks 65-35-6, 5#/sack gilsonite and 2% CaCl2 (yield 1.87, weight 12.7). Tailed in with 200 sacks Class C 2% CaCl2 (yield 1.34, weight 14.8). PD 4:15 AM 4-14-96. Bumped plug to 800 psi, OK. Cement did not circulate. WOC 6 hours. Ran Temperature Survey and found top of cement at 120'. Ran 1". Tagged cement at 120'. Spotted 100 sacks Class C 4% CaCl2. PD 11:30 AM 4-14-96. WOC 1 hour. Ran 1". Tagged cement at 25'. Spotted 150 sacks Class C 4% CaCl2. PD 12:50 PM 4-14-96. WOC. Nippled up and tested to 1000 psi for 30 minutes, OK. Drilled out at 6:15 AM 4-16-96. WOC 50 hours. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE 4-25-96

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

SUPERVISOR, DISTRICT II

APR 30 1996

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: