

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-28879

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Dayton FP

8. Well No.

2

9. Pool name or Wildcat

Atoka San Andres

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter G : 1650 Feet From The North Line and 1750 Feet From The East Line

Section 21

Township 18S

Range 26E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3360' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 1150'. Reached TD at 2:30 PM 4-8-96. Ran 26 joints of 8-5/8" 24# J-55 (1149.53') of casing set at 1148'. 1-Texas Pattern notched guide shoe set at 1148'. Insert float set at 1105'. Cemented with 100 sacks "H", 10% A-11, 5#/sack gilsonite, 1/4#/sack celloseal and 1% CaCl2 (yield 1.51, weight 14.6) and 275 sacks 65-35-6, 5#/sack gilsonite, 1/4#/sack celloseal and 2% CaCl2 (yield 1.87, weight 12.7). Tailed in with 200 sacks Class C 2% CaCl2 (yield 1.34, weight 14.8). PD 8:15 PM 4-8-96. Bumped pipe OK. Circulated 36 sacks. WOC. Nipped up and tested to 1000 psi for 15 minutes. Drilled out at 11:15 AM 4-9-96. WOC 15 hours. Reduced hole to 7-7/8". Resumed drilling.

RECEIVED

APR 15 1996

OIL CON. DIV.
DIST. 2

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Production Clerk

DATE

4-11-96

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY

TITLE

DATE

APR 17 1996

CONDITIONS OF APPROVAL, IF ANY: