

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Premier Sand San Andres	1192' 1228'	1228' 2006'	Sandstone Dolomite	Queen Grayburg Premier San Andres	588' 967' 1192' 1228'	+2844 +2465 +2240 +2204
		DEPTH	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.. (continued from the front)			
		1742-1996'	15,000 gals PrePad + 2 drum Pro-Kem scale inhibitor + 53,000 gals 30# X-link gel water + 7000# 100 mesh sand + 284,000# 20/40 brady sand and 16/30 sand			
		1194-1574'	1500 gals of 15% NeFe acid			
		1194-1574'	1,000 gals gel PrePad + 2 drum Pro-Kem scale inhibitor + 12,000 gals 30# X-link gelled 2% KCL water + 40,000# 20/40 Brady sand & 8,000# 16/30 CRC sand			