

Submit to Appropriate District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-105
Revised 1-1-89

6157
Blm
Boym
Stld

WELL API NO. 30-015-28989
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. X-00703
7. Lease Name or Unit Agreement Name S.A. Solt
8. Well No. 3
9. Pool name or Wildcat Artesia; ON-GB-SA

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐

b. Type of Completion: NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RESVR ☐ OWNER ☐

2. Name of Operator
SDX Resources, Inc.

3. Address of Operator
PO Box 5061, Midland, TX 79704

4. Well Location
Unit Letter K : 2304 Feet From The South DIST 2 2269 Feet From The West Line

Section <u>5</u>	Township <u>18S</u>	Range <u>28E</u>	NMPM	Eddy	County
10. Date Spudded 6-5-96	11. Date T.D. Reached 6-14-96	12. Date Compl. (Ready to Prod.) 7-10-96	13. Elevations (DF & RKB, RT, GR, etc.) 3653' GR	14. Elev. Casinghead	
15. Total Depth 2850'	16. Plug Back T.D. 2812'	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By Rotary Tools X	Cable Tools	
19. Producing Interval(s), of this completion - Top, Bottom, Name 1983' - 2428'			20. Was Directional Survey Made Yes		
21. Type Electric and Other Logs Run CNL-GR-CCL			22. Was Well Cored No		

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24# J-55	380'	12-1/4"	350 sx Cl C 2% CaCl	
5-1/2"	14# J-55	2846'	7-7/8"	210 sx 65/35 POZ Lite	
				+ 300 sx 50/50 POZ Lite	

24. LINER RECORD					25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2-3/8"	2509'	

26. Perforation record (interval, size, and number) 1983', 84, 87, 88, 2025, 37, 43, 54, 55, 56, 59 86, 87, 2141, 42, 48, 49, 64, 65, 74, 75, 82, 83, 2370, 71, 2383, 84, 90, 91, 2412, 26, 27, 28, (33 holes)	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.	
	DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
	1983-2428	A: 4730 gal NEFE F: 40000 gal XL gel + 120,000# 16/30 sd

28. PRODUCTION							
Date First Production 7-9-96		Production Method (Flowing, gas lift, pumping - Size and type pump) 2" x 1-1/2" x 10' RWAC pump				Well Status (Prod. or Shut-in) Prod.	
Date of Test 7-21/96	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 20	Gas - MCF 10	Water - Bbl 6	Gas - Oil Ratio 500
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl 20	Gas - MCF 10	Water - Bbl 6	Oil Gravity - API - (Corr.) 38.5	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)
Sold

30. List Attachments
Logs, deviation rpt

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature Bonnie Atwater Printed Name Bonnie Atwater Title Regulatory Asst. Date 7-29-96

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	
T. Salt	410'
B. Salt	460'
T. Yates	
T. 7 Rivers	1130'
T. Queen	1600'
T. Grayburg	1880'
T. San Andres	2186'
T. Glorieta	
T. Paddock	
T. Blinebry	
T. Tubb	
T. Drinkard	
T. Abo	
T. Wolfcamp	
T. Penn	
T. Cisco (Bough C)	

T. Canyon _____
T. Strawn _____
T. Atoka _____
T. Miss _____
T. Devonian _____
T. Silurian _____
T. Montoya _____
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash _____
T. Delaware Sand _____
T. Bone Springs _____
T. _____
T. _____
T. _____
T. _____

Northwestern New Mexico

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn "A" _____

T. Penn. "B" _____
T. Penn. "C" _____
T. Penn. "D" _____
T. Leadville _____
T. Madison _____
T. Elbert _____
T. McCracken _____
T. Ignacio Otzte _____
T. Granite _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....

No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology
0	385'	385'	Anhydrite
385	1958	1573'	Dolomite/Anhydrite
1958	2850	892'	Dolomite