Form 3160-5 (June 1990)

any matter within its jurisdiction

) STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

N.M. Oil ... ns. Division 811 S. 1st Street FORM APPROVED Artesia, NM 88210-2834 Gget Bureau No. 1004-0135

C151	
------	--

Expires March 31, 1993 SUNDRY NOTICES AND REPORTS ON WELLS 5. Lease Designation and Serial No. Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. C-070678-A Use "APPLICATION FOR PERMIT—" for such proposal FP 6 If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 1. Type of Well Unit or CA, Agreement Designation ⊠ Oil Well ☐ Gas Well Other 2. Name of Operator Well Name and No. **DEVON ENERGY CORPORATION (NEVADA)** Federal #3 API Well No. 3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235330-015-29014 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 10. Field and Pool, or Exploratory Area 2310' FSL & 1650' FWL (K) of Section 8-T18S-R27E Red Lake (Q-GB-SA) 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Completion Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 8/27/96 RU Wedge WL. Ran Bond log from 2144' - 50'. Perf'd w/1 SPF as follows: 1567', 78', 1600', 02', 26', 47', 1731', 42', 1755', 78', 84', 1802', 04', 24', 34', 41', 54', 82', 1904', 14', 22', 32', 40', 48', 54', 64', and 66', for a total of 27 holes (.40 EHD Holes). Acidize San Andres perfs 1567-1966' w/2500 gals of 15% NeFe acid, ISIP 1000#. Frac'd perfs 1567-1966' w/1,000 gals PrePad + 2 drum Pro-Kem scale inhibitor + 180,000 gals gel water + 6000# 100 mesh sand + 237,000# 20/40 Brady sand. ISIP 1400#, closed at 1159#. Ran 2 7/8" production tbg, SN set at 2118'. Ran pump and rods. Began pump testing. 14. I hereby certify that the foregoing is true and correct Diana Keys Title Engineering Technician Date September 16, 1996 (This space for Federal or State office use) Approved by Title Conditions of approval, if any: Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the united States any false, fi