Form 3160-5

N.M. Oil ns. Division

(June 1990)	DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT	811 S. 1st Street Artesia, NM 88210-	PORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 ST. Lesse Designation and Serial No.
Do not use this form for	PRY NOTICES AND REPORTS ON proposals to drill or to deepen or reer PLICATION FOR PERMIT—" for such	WELLS	NM-0437522
	SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
1. Type of Well Oil Gas Other			
2. Name of Operator		12.5	8. Well Name and No. #2 EAST TURKEY TRACK FED COM
MYCO INDUSTRIES, 1 3. Address and Telephone No. P.O. BOX 840, ARTE		7.2 Maria	9. API Well No. 30-015-29022
4. Location of Well (Footage, Sec., T.,		a Carried Co	10. Field and Pool, or Exploratory Area
1880' FNL & 990' F	TUT	1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	N. TURKEY TRACK MORROW
Sec. 26-T18S-R29E	WL		11. County or Parish, State GAS
12. CHECK APPRO	PRIATE ROY(e) TO INDICATE MAT	TUDE OF NOTICE TO	EDDY, NEW MEXICO
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION			
Notice of Intent	Abendoo	TYPE OF ACTION	
	- Abundon		Change of Plans New Construction
Subsequent Report	Plugging		Non-Boutine Fracturing
Final Abandonment !	Notice Casing R	•	Water ShuttOff
	, , ,	NTERMEDIATE CASING	Conversion to Injection C
0.00			(Note: Report resultant multiple completion on Wall
give subsurface locations and me	ations (Clearly state all pertinent details, and give pertinen assured and true vertical depths for all markers and zones	t dates, including estimated date of starting s pertinent to this work.)*	any proposed work. Masell is directionally drilled.
4:15 AM	 .	•	
7/23/96 TD @ 3200'	with 12½" Hole.		က်ကို က
	with BLM of Casing & Cementi		
Ran 81-Jts 8 5/8", (Total CSG. 3207.18	32#, J-55 8rd ST&C Casing wi '). Insert Float Collar at	th Regular Guide Sho	pe set at 3200'
CMT with 1200sx. "C" Tailed in with 200-s	" Lite + 5#/sx Gilsonite + ½ sx "C" + 2% Cacl2 (Yld1.32	 #/sx Celloseal (Y1d- Wt14.8)	2.05 Wt12.5)
7/24/96 5:45 PM Plug held 1200 PST a	and Circulated 150sx CMT. to 2500 PSI. Tested Manifol		sted to 5000 PSI. circulation
WOC 18-Hrs. Drille CERTIFIED RETURN: P	d out at 11:30 AM 7/24/96 wi	th 7 7/8" Bit.	
4. I hereby certify that the foregoing is tr	we and correct		
Signed Statut	Lopey Title ENGINI	ERING TECHNICIAN	Date _7/24/96
(This space for Federal or State office	use)	ED TOR IN CORD	
Approved by	Tirle Tirle	att Exall	Date