Form 3160-5 (June 1990)

## UNI D STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M. O' ons. Division 811 S. 1s: Street Artesia, NM 88210-2834 FORM APPROVED

C158

Budget Bureau No. 1004-0135 Expires March 31, 1993 55 SUNDRY NOTICES AND REPORTS ON WELLS 5. Lease Designation and Serial No. Do not use his form for proposals to drill or to deepen or reentry to a different reservoir. NM-031186 Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE ARE 7. If Unit or CA, Agreement Designation 1. Type of Well ☐ Other \_\_\_\_ 8. Well Name and No. 2. Name of Operator **DEVON ENERGY CORPORATION (NEVADA)** Hawk "9E" Federal #5 3. Address and Telephone No. 9. API Well No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73 30-015-29025 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 1650' FNL & 330' FWL of Section 9-18S-27E; "E" Red Lake (Q-GB-SA) 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Notice of Intent Change of Plans Abandonment Recompletion **New Construction** Plugging Back Non-Routine Fracturing Subsequent Report Water Shut-Off Casing Repair Conversion to Injection Final Abandonment Notice Altering Casing Dispose Water Other spud, csg strings & TD. (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* We spud this well on 8/14/96 at 1440 hrs and drld a 12 1/4" hole to 1100'. On 8/16/96 ran 27 jts 8 5/8" 24# J-55 ST&C csg, set at 1095'. Cemented w/300 sxs 35/65 poz "C" & 200 sxs "C". Circ'd 55 sxs cmt. Drld 7 7/8" hole and reached TD 2411' on 8/18/96 at 1600 hrs. Schlumberger ran LDT/CNL/DLL/MSFL/GR logs. Ran 56 its 5 1/2" 15.5# J-55 LT&C csg, set at 2410'. Cemented w/150 sx lite "C" + 275 sx Class "C". Circ'd 43 sxs cmt. Released rig at 0300 hrs 8/19/96. WOCU. **OCT** 2.5 5.06 C. Clover 14. I hereby certify that the foregoing is true and correct Diana Keys Date September 24, 1996 Title Engineering Technician Approved by Title Date Conditions of approval, if any: