

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE

FORM APPROVED


N.M. Cons. Division

811 S. 1st Street
Artesia, NM 88210-2834

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. TYPE OF WELL:		OIL WELL ☒	GAS WELL ☐	DRY ☐	Other		
b. TYPE OF COMPLETION:		NEW WELL ☐	WORK OVER ☐	DEEP-EN ☒	PLUG BACK ☐	DIFF. RESVR ☐	Other
2. NAME OF OPERATOR DEVON ENERGY PRODUCTION COMPANY, LP.						6. IF INDIAN, ALLOTTEE OR TRIBE NAME NA	
3. ADDRESS AND TELEPHONE NO. 20 N. BROADWAY, SUITE 1500, OKC, OK 73102-8260 (405) 235-3611						7. UNIT AGREEMENT NAME NA	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements) At surface 890' FSL & 940' FEL, Unit "P" At top prod. interval reported below (Same) At total depth (Same)						8. FARM OR LEASE NAME, WELL NO. Hawk 8 P Federal #11	
14. PERMIT NO.						9. API WELL NO. 30-015-29027	
DATE ISSUED 9/23/99						10. FIELD AND POOL, OR WILDCAT Red Lake(Q-GB-SA) & Glorieta-Yeso	
12. COUNTY OR PARISH Eddy County						13. STATE NM	
15. DATE SPUDDED 5/31/00		16. DATE T.D. REACHED 6/4/00		17. DATE COMPL. (Ready to prod.) 6/21/00		18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* KB 3463'; GL 3454'; DF 3462'	
19. ELEV. CASINGHEAD		20. TOTAL DEPTH, MD & TVD 4000'		21. PLUG, BACK T.D., MD & TVD 3954'		22. IF MULTIPLE COMPL., HOW MANY*	
23. INTERVALS DRILLED BY →		24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* San Andres 1646'-2140', Yeso 2940'-3562' (Well deepened to Yeso 6/00 and downhole commingled with existing San Andres perfs effective 6/22/00 per NMOCD Administrative Order DHC-2658).		25. WAS DIRECTIONAL SURVEY MADE No		26. TYPE ELECTRIC AND OTHER LOGS RUN Dual Laterolog Gamma Ray, Slim Access Litho-Density CNL/GR	
27. WAS WELL CORED No		28. CASING RECORD (Report all strings set in well)					
CASING SIZE/GRADE		WEIGHT, LB./FT.		DEPTH SET (MD)		HOLE SIZE	
8-5/8 J-55		24#		1096		12-1/4"	
5-1/2" J-55		15.5#		2346		7-7/8"	
29. LINER RECORD		30. TUBING RECORD		SIZE		DEPTH SET (MD)	
SIZE		TOP (MD)		BOTTOM (MD)		SACKS CEMENT*	
4"		2246'		4000'		90	
31. PERFORATION RECORD (Interval, size and number) SANANDRES, ALPHA, "A", "B", "C", & "D" 1646'-2140' (18 holes) — Existing perfs YESO 2940'-3562' (37 holes) — Deepened to Yeso 6/00 and downhole commingled w/ existing San Andres perfs effective 6/22/00.		32. ACID SHOT, FRACTURE, CEMENT SQUEEZE, ETC.		DEPTH INTERVAL (MD)		AMOUNT AND KIND OF MATERIAL USED	
2940'-3205'		1500 gals 15% NEFE acid		2940'-3205'		6000 gals slick wtr prepad + 48,000 gal linear Gel wtr + 2000# 100 mesh sd + 37,000# 20/40 Brady sd + 9000# CRC sd	
33.* PRODUCTION		DATE FIRST PRODUCTION 6/22/00		PRODUCTIONS METHOD I(Flowing, gas lift, pumping—size and type of pump) Pumping (2-1/16" x 1-1/2" x 20' RWTC pump)		WELL STATUS (Producing or shut-in) Producing	
DATE OF TEST 9/1/00		HOURS TESTED 24		CHOKE SIZE		PROD'N FOR TEST PERIOD →	
OIL-BBL. 23		GAS-MCF. 20		WATER-BBL. 124		GAS-OIL RATIO 870/1	
FLOW. TUBING PRESS.		CASING PRESSURE		CALCULATED 24-HOUR RATE →		OIL-BBL. 23	
GAS-MCF. 20		WATER-BBL. 124		OIL GRAVITY-API (CORR.) 40		TEST WITNESSED BY Danny Hokett	
34. DISPOSITION OF GAS (Solid, used for fuel, vented, etc.) Sold		35. LIST OF ATTACHMENTS Logs, deviation surveys					
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records		(ORIG. SGD.) GARY GOURLEY					

SIGNED

TONJA RUTELONIS
TITLE ENGINEERING TECHNICIAN

DATE 9/12/00

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Premier sand	1235'	1332'	sandstone dolomite sd & dolomite dolomite	Bowers	480'	
San Andres	1332'	2762'		Queen	674'	
Glorieta	2762'	2896'		Grayburg	991'	
Yeso	2896'	4000'		Premier	1235'	
			San Andres	1332'		
			Glorieta	2762'		
				Yeso	2896'	
		DEPTH	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.. (continued from the front)			
		3496'-3562'	1500 gals 15% NEFE acid			
		3496'-3562'	6000 gals slick wtr prepad + 42,000 gals linear gel wtr + 2000# 100 mesh sd + 37,000#			
			20/40 Brady sd + 9000# CRC sd			

Hawk 8 P Federal #11
890' FSL & 940' FEL
Section 8-18S-27E
Eddy County, NM

The following are deviation surveys for the above well:

<u>DEPTH</u>	<u>DEVIATION</u>
2483'	0°
2966'	0°
3479'	2°
3970'	1°