

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Conservation Division
811 S. 1st Street
Artesia, NM 88210-2834

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other -----

2. Name of Operator

DEVON ENERGY CORPORATION (NEVADA)

3. Address and Telephone No.

20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FNL & 2210' FEL of Section 4-18S-27E, Lot 4

5. Lease Designation and Serial No.

NM-033825

6. If Indian, Allottee or Tribe Name

NA

7. If Unit or CA, Agreement Designation

NA

8. Well Name and No.

Hondo Federal #4

9. API Well No.

30-015-29051

10. Field and Pool, or Exploratory Area

Red Lake (Q-G-SA)

11. County or Parish, State

Eddy County, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud, Casing strings, TD

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded this well on 10/29/96 at 1400 hrs and drld a 12 1/4" hole to 1118'. On 10/31/96 ran 27 jts 8 5/8" 24# J-55 ST&C csg, set at 1118'. Cemented w/100 sxs cl "C" + 300 sx lite "C" + 200 sx Class "C". Circ'd 0 sxs cmt, TOC @ 30'. (ready mix to surface per BLM specifications, TOC @ surface)

Drld 7 7/8" hole and reached TD 2400' on 11/2/96 at 1900 hrs. Schlumberger ran LDT/CNL/DLL/MSFL/GR logs. Ran 56 jts 5 1/2" 15.5# J-55 LT&C csg, set at 2399'. Cemented w/275 sx lite "C" + 300 sx Class "C". Circ'd 106 sxs cmt.

Released rig at 1600 hrs 11/3/96. WOCU.

NOV 18 1996

RECEIVED
NOV 15 9 56 AM '96

14. I hereby certify that the foregoing is true and correct

Diana Keys

Signed

Diana M Keys

Title Engineering Technician

Date November 7, 1996

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: