Form 3160-5 (November 1983)

UNITED J'ATES (Formerly 9-331) DEPARTMENT OF THE INTERIOR

N.M. Oil Cons. Philision

8110 Surf Ri FRIA CATE * Budget Bureau No. 1004-0135
Arte Size riverse side \ Expires August 31, 1985

	BUREAU OF LAND MANAGEMENT			reverse state y	5. LEASE DESIGNATION AND SERIAL NO. LC-029420-B		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT - " for such proposals.")					6. IF INDIAN, ALLOTTEE OR TRI	BE NAME	
OIL WELL		OTHER	0	green	7. UNIT AGREEMENT NAME Skelly Unit		
2. NAME OF OPERATOR The Wiser Oil Company					8. API WELL NO. 30-015-29064		
3. ADDRESS OF OPERATOR					9. WELL NO.		
P. O. Box 2568 Hobbs, New Mexico 88241					272 10. FIELD AND POOL, OR WILDCAT		
 LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) 					Grayburg Jackson 7-Rivers		
At surface 1213' FNL & 1428' FWL					11. SEC., T., R., M., OR BLK. AN		
Sec. 28-T17S-R31E					D		
Unit C					SURVEY OR AREA		
					Sec. 28-T17S-R31E	T 13. STATE	
14. PERMIT NO		15. ELEVATIONS (Show who	ther DF, R	T, GR, etc.)	12. COUNTY OR PARISH Eddy	NM	
/	Ot -1 /		to Motor	of Notice Papert or Othe		14141	
16. Check Appropriate Box to indicate Nature of Notice, Report, or Other					Ci Data		
NOTICE OF INTENTION TO:					BSEQUENT REPORT OF:		
TEST WATER SHUT	OFF	PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRING WELL		
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING CASING	; 	
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING	G ABANDONMENT *	\\ ==	
REPAIR WELL		CHANGE PLANS		(Other) Spudding, Ceme	enting Surface & Production C	asing	
1				(Note: Report results of	of multiple completion on Well		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) MIRU Norton Drilling Co., Rig #7. Spudded 12-1/4" surface hole @ 5:15 p.m., 09/14/96. Drilled hole to 442'. Ran 10 jts. 8-5/8", 23#, K-55, LT& C csg. Set at 439'. Halliburton cemented with 325 sx. Class "C" containing 1/4#/sk. Flocele + 2% CaCl. Plug down @ 2:00 a.m, 09/15/96. Circulated 76 sx. cmt. BLM was notified, no representative present. NU BOP & tested csg. to 1000# for 30 minutes, no pressure loss. WOC 12 hrs. Drilled 7-7/8" production hole to a depth of 3987'. Ran logs and elected to run casing. Ran 95 jts. 5-1/2" 17#, J-55, LT&C csg. Set at 3987'. Halliburton cemented w/1000 gals. Superflush 102 + 900 sx. Halliburton Lite + 8# salt/sk.							
+ 1/4# Flocele w/1 bbl. FW + Pressure tested notified, no rep	/sk. followed - 12 bbls. MSA I casing to 150 presentative pro-	by 250 sx. Premium Pla A + 79 bbls. FW w/Lo-S 0# for 30 minutes, no p esent.	us w/3#1 Surf 300	KCL/sk. + .5% Halad 34). Plug down @ 3:15 a.n	1 sx. Halliburton Lite + 8# sa 14 + 1/4# Flocele/sk. Displac 1. 09/20/96. Circ. 102 sx. cm 1.5 a.m. 09/20/96. BLM was	æd	
18 I hereby certify that th	e foregoing is true a	nd correct.					
SIGNED	go Tueney	TITLED	rilling I	Department	DATE September 2	23 <u>, 1996</u>	
(This space for Federal	or State office use)		/ YOU		1		
APPROVED BY		TITLE	1.	net 6 4 1960 1 1	DATE	<u>.</u>	
CONDITIONS OF API	PROVAL, IF ANY:		11	((DRIG. SGD.) GARY GOURI	.EY	
		*See Ir	struction	On Reverse Side	=		