Form 3160-5 (June 1990)

Conditions of approval, if any:

UNI) STATES DEPARTMEN 1 OF THE INTERIOR BURFALLOF LAND MANAGEMENT

d51-

BUREAU OF LAND MANAGEMENT **FORM APPROVED** Budget Bureau No. 1004-0135 Expires March 31, 1993 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. NM 033825 Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well NOV 1 3 1996 П ☐ Other ____ 8. Well Name and No. 2. Name of Operator **DEVON ENERGY CORPORATION (NEVADA)** Hondo Federal #3 3. Address and Telephone No. 9. API Well No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73402 (405) 235-3611 30-015-29065 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 10. Field and Pool, or Exploratory Area 430' FNL & 890' FEL of Section 4-18S-27E, Lot 5 Red Lake (Q-G-SA) 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off ☐ Final Abandonment Notice Altering Casing Conversion to Injection Other Spud, Casing strings, TD Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded this well on 10/17/96 at 1230 hrs and drld a 12 1/4" hole to 1074'. On 10/19/96 ran 27 its 8 5/8" 24# J-55 ST&C csg, set at 1074'. Cemented w/300 sx lite "C" + 200 sx Class "C". Circ'd 73 sxs cmt. Drld 7 7/8" hole and reached TD 2500' on 10/21/96 at 1600 hrs. Schlumberger ran LDT/CNL/DLL/MSFL/GR logs. Ran 59 jts 5 1/2" 15.5# J-55 LT&C csg, set at 2499'. Cemented w/150 sx lite "C" + 400 sx Class "C". Circ'd 28 sxs cmt. ACCEPTED FOR RECORD Released rig at 1530 hrs 10/22/96. WOCU. PLM 14. I hereby certify that the foregoing is true and correct Diana Keys Title Engineering Technician Date October 24: 1996 Approved by